

UNIVERSITÀ POLITECNICA DELLE MARCHE Repository ISTITUZIONALE

Comparison of the new Cl2/O3/UV process with different ozone- and UV-based AOPs for wastewater treatment at pilot scale: Removal of pharmaceuticals and changes in fluorescing organic matter

This is the peer reviewd version of the followng article:

Original

Comparison of the new Cl2/O3/UV process with different ozone- and UV-based AOPs for wastewater treatment at pilot scale: Removal of pharmaceuticals and changes in fluorescing organic matter / Sgroi, M.; Anumol, T.; Vagliasindi, F. G. A.; Snyder, S. A.; Roccaro, P.. - In: SCIENCE OF THE TOTAL ENVIRONMENT. - ISSN 0048-9697. - ELETTRONICO. - 765:(2021). [10.1016/j.scitotenv.2020.142720]

Availability:

This version is available at: 11566/297397 since: 2024-04-22T13:55:18Z

Publisher:

Published DOI:10.1016/j.scitotenv.2020.142720

Terms of use:

The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. The use of copyrighted works requires the consent of the rights' holder (author or publisher). Works made available under a Creative Commons license or a Publisher's custom-made license can be used according to the terms and conditions contained therein. See editor's website for further information and terms and conditions. This item was downloaded from IRIS Università Politecnica delle Marche (https://iris.univpm.it). When citing, please refer to the published version.

note finali coverpage

(Article begins on next page)

Comparison of the new Cl2/O3/UV process with different ozoneand UV-based AOPs for wastewater treatment at pilot scale: Removal of pharmaceuticals and changes in fluorescing organic matter



Massimiliano Sgroi, Tarun Anumol, Federico G.A. Vagliasindi, Shane A. Snyder, Paolo Roccaro

PII:	S0048-9697(20)36249-5
DOI:	https://doi.org/10.1016/j.scitotenv.2020.142720
Reference:	STOTEN 142720
To appear in:	Science of the Total Environment
Received date:	7 August 2020
Revised date:	27 September 2020
Accepted date:	27 September 2020

Please cite this article as: M. Sgroi, T. Anumol, F.G.A. Vagliasindi, et al., Comparison of the new Cl2/O3/UV process with different ozone- and UV-based AOPs for wastewater treatment at pilot scale: Removal of pharmaceuticals and changes in fluorescing organic matter, *Science of the Total Environment* (2020), https://doi.org/10.1016/j.scitotenv.2020.142720

This is a PDF file of an article that has undergone enhancements after acceptance, such as the addition of a cover page and metadata, and formatting for readability, but it is not yet the definitive version of record. This version will undergo additional copyediting, typesetting and review before it is published in its final form, but we are providing this version to give early visibility of the article. Please note that, during the production process, errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

© 2020 Published by Elsevier.

Comparison of the new Cl₂/O₃/UV process with different ozone- and UV-based AOPs for wastewater treatment at pilot scale: Removal of pharmaceuticals and changes in fluorescing organic matter

Massimiliano Sgroi¹, Tarun Anumol^{2,3}, Federico G.A. Vagliasindi¹, Shane A. Snyder^{3,4,*}, Paolo

Roccaro^{1,**}

¹ Department of Civil Engineering and Architecture, University of Catania, Viale A. Doria 6, 95125, Catania, Italy

² Agilent Technologies Inc., 2850 Centerville Road, Winnirgton, DE 19808, USA

³ Department of Chemical and Environmental E. gincering, University of Arizona, 1133 E. James E. Rogers Way, Tucson, AZ, 85721, USA

⁴ Nanyang Technological Universit_j; Nanyang Environment & Water Research Institute, 1 Cleantech Loop, CleanTech One, #25-08, 637141, Singapore

* Corresponding author. Phone: +1 520 6212573; fax: +1 520 6216048; e-mail address: snyders2@email.arizona.e lu

** Corresponding author. Phone: +39 095 738 2704; fax: +39 095 738 2748; e-mail address: proccaro@dica.unict.it

ABSTRACT

This work critically compared the removal of fluorescing PARAFAC components and selected pharmaceuticals (carbamazepine, fluoxetine, gemfibrozil, primidone, sulfamethoxazole, trimethoprim) from a tertiary wastewater effluent by different UV- and ozone-based advanced oxidation processes (AOPs) operated at pilot-scale. Investigated AOPs included UV/H₂O₂, UV/Cl₂, O₃, O₃/UV, H₂O₂/O₃/UV, and the new Cl₂/O₃/UV. AOPs comparison was accomplished using various ozone doses (0 - 9 mg/L), UV fluences $(191 - 981 \text{ mJ cn}^2)$ and radical promoter concentrations of $Cl_2 = 0.04$ mM and $H_2O_2 = 0.29$ mM. Chlorin -ba ed AOPs produced radical species that reacted more selectively with pharmaceuticals than radical species and oxidants generated by other AOPs. Tryptophan-like substances and humic-like fluorescing compounds were the most degraded components by all AOPs, which vere better removed than microbial products and fulvic-like fluorescing substances. Removal of UV absorbance at 254 (UV₂₅₄) nm was always low. Overall, chlorine-based AOPs ver nore effective to reduce fluorescence intensities than similar H_2O_2 -based AOPs. The $C_2/O_3/UV$ process was the most effective AOP to degrade all target micro-pollutants except princidone. On the other hand, the oxidation performance of pharmaceuticals by other ozo ve-b sed AOPs followed the order $H_2O_2/O_3/UV > O_3/UV > O_3$. UV/Cl₂ process outcompeted UV/H₂O₂ only for the removal of trimethoprim and sulfamethoxazole. Correlations between the removal of pharmaceuticals and spectroscopic indexes (PARAFAC components and UV_{254}) had unique regression parameters for each compound, surrogate parameter and oxidation process. Particularly, a diverse PARAFAC component for each investigated AOP resulted to be the most sensitive surrogate parameter able to monitor small changes of pharmaceuticals removal.

Keywords: contaminants of emerging concern (CEC); micro-pollutants; ozone/chlorine; UV/chlorine; fluorescence spectroscopy; on-line monitoring

1. Introduction

In recent years, contaminants of emerging concern (CEC) such as pharmaceuticals, personal care products, pesticides, and industrial chemicals have been detected and extensively investigated in different water matrices, including wastewater, surface water and a inking water (Benotti et al., 2009; Dickenson et al., 2011; Focazio et al., 2008). Partice water and a inking water treatment plants (WWTPs) have been recognized as significant hotspots for the transfer of CEC into the environment (Michael et al., 2013; Sgroi et al., 2017a, 2017b). Furthermore, extensive studies have shown that some of these contaminants can have a significant and ternes, 2009; Richardson and Ternes, 2018).

Traditional WWTPs usually utilize only primary and secondary treatments, with the latter often based on conventional activated sludge. These treatments tend to provide poor removal for most CEC in wastewater, and thus dvanced/tertiary treatment methods are necessary to achieve an effective removal of these inicro-pollutants (Guillossou et al., 2020; Roccaro et al., 2013; 2018; Villarín and Merel, 2020). Advanced oxidation processes (AOPs) are effective technologies for the removal of refractory micro-pollutants, such as pharmaceuticals, via the generation of reactive radicals, such as hydroxyl radical (^{*}OH) (Rizzo et al., 2019; Wang and Zhuan, 2020). There are various different process technologies that have been investigated for use as AOPs. Several AOPs, especially those involving ozonation and UV irradiation (e.g., O₃, O₃/H₂O₂, UV/H₂O₂) are already well established and operated at full-scale in drinking water treatment and water reuse

facilities (Gogate and Pandit, 2004; Liu et al., 2019b; Miklos et al., 2018b). However, studies of numerous emerging AOPs for water treatment (e.g., UV/chlorine, UV/persulfate, UV/CaO₂) are constantly being reported by various researchers (Mehrjouei et al., 2015; Miklos et al., 2018b; Zheng et al., 2019). The general aim of those studies is the development of oxidation processes that should be highly effective for micro-pollutants degradation and economically sustainable (Gogate and Pandit, 2004; Miklos et al., 2018b). Further aim of researchers is the development of water treatment technologies able to completely mineralize macro-pollutants, and avoid the production of transformation substances with higher toxicity u.c., parent compounds (W. L. Wang et al., 2018). The latter scope is often reached by the use of biofiltration or adsorption after the AOP (Magdeburg et al., 2014).

The UV/chlorine (UV/Cl₂) process is an emerging and attractive AOP for water and wastewater treatment, which is able to produce different radical species, including 'OH and reactive chlorine species (RCS) (i.e., Cl⁺, Cl⁺₂, ClO⁺) (Cerreta et al., 2020; Guo et al., 2018, 2017). RCS are very powerful oxidants that are produced with much higher yield than 'OH during UV irradiation (Guo et al., 2018, 2017). However, RCS are selective oxidants, and preferentially react with electron-rich moieties containing olefins, phenols, anilines, and alkyl-/alkoxybenzenes (Guo et al., 2018, 2017; Lei et al. 2019). On the contrary, electron-withdrawing compounds, such as primidone, ronidazole and ibuprofen, are better removed by hydroxyl radicals, which are nonselective oxidants (Guo et al., 2018, 2017; Miklos et al., 2019). Studies have also reported that UV/Cl_2 process is less affected by the water and wastewater matrices than UV/H_2O_2 , and that UV/Cl_2 is a more economical process than UV/H_2O_2 (Guo et al., 2018; Miklos et al., 2018b).

Ozone is a commonly used disinfectant and oxidant in water and wastewater treatment. During conventional ozonation, CEC can be oxidized by O_3 and/or by hydroxyl radicals that are gener-

ated from O_3 decomposition in real water matrices (von Sonntag and von Gunten, 2012). O_3 is a selective oxidant and reacts preferentially with organics that have olefins, activated aromatic systems, or amines (von Sonntag and von Gunten, 2012). Hence, many ozone-resistant CEC that can only be oxidized by 'OH are less efficiently abated during conventional ozonation. Methods to enhance the formation of hydroxyl radicals include the combinations O_3/H_2O_2 (also called peroxone-process), O_3/UV , and $H_2O_2/O_3/UV$ (Liu et al., 2019a, 2019b; H. Wang et al., 2018; Yao et al., 2018). However, benefits from the combination of $O_{3/2} O_2$, and O_3/UV have been shown to be limited in wastewater matrices due to the fast reaction of ozone with dissolved organic matter (DOM) moieties, and the high scavenging ethod for 'OH radicals (Lado Ribeiro et al., 2019; Miklos et al., 2018b; H. Wang et al., 2018). C. the contrary, much higher 'OH yields and micro-pollutants abetment have been observid vhen combining H₂O₂/O₃/UV (Liu et al., 2019b, 2019a). Furthermore, the presence of \mathbb{P}_2O_2 in ozone-based AOPs reduce the formation of bromate (Von Gunten and Oliveras, 1928). The above summarized results were produced by several studies that investigated and compared oxidant exposures and micro-pollutants removal by different ozone-based and U V-based AOPs. However, those comparative studies have mainly been accomplished at laboratory scale, and similar comparisons at pilot scale are very scarce in the literature, particularly for the chlorine-based AOPs. In this study, we critically discussed the removal of different pharmaceuticals during treatment at pilot scale of a wastewater effluent by various AOPs, which included UV/H₂O₂, UV/Cl₂, O₃, O₃/UV, and H₂O₂/O₃/UV. Furthermore, we investigated a new AOP that has never been applied to wastewater treatment previously, and it is the combination of $Cl_2/O_3/UV$. Particularly, a recent study has shown that the combination of ozone and chlorine was able to improve the removal of dodecylbenzyldimethylammonium chloride in deionized (DI) water due to the increased yield of 'OH and the formation of others

reactive oxidants, which can be classified as RCS, compared to conventional ozonation (Huang et al., 2020).

Diverse AOPs can be discriminated by the produced oxidant/radical species (e.g., 'OH, Cl', Cl⁻₂, Clo', SO_4'), and by the yield of those produced radicals (Guo et al., 2017; von Sonntag and von Gunten, 2012). The oxidants exposure in water/wastewater can be evaluated by monitoring the degradation kinetics of probe compounds, which are generally selected according to their reactivity with the investigated oxidants/radical species (Guo et 71, 2018; von Sonntag and von Gunten, 2012). A further approach useful to compare the oxi 'atic's potential of different AOPs in natural water/wastewater is the investigation of the reactive y of the produced/used oxidants with different DOM moieties (Cruz-Alcalde et al., 2010: Merei et al., 2015; Miklos et al., 2018a; Varanasi et al., 2018; Wenk et al., 2013; Wenterhoft et al., 2007). Fluorescence excitation emission matrix (EEM) is a fast and sensitive technique able to characterize bulk organic matter in natural and engineered aquatic system. (Carstea et al., 2016). EEM of natural water and wastewater tend to have distinct features with maxima located at characteristic combinations of excitation and emission wavele. oths, and this spectroscopic technique has been shown to be very useful for discriminating between different source and components of DOM (Carstea et al., 2016; Korshin et al., 2015). Thus, fluorescence spectroscopy is highly attractive to investigate the degradation of DOM during different AOPs (Chen et al., 2017). In addition, fluorescence measurements have been suggested as suitable surrogate parameters to predict the removal of pharmaceuticals during conventional and advanced wastewater treatments (Korshin et al., 2018; Miklos et al., 2019; Sgroi et al., 2017a). Nevertheless, since diverse fluorescence components may have different reactivity with different oxidants, different fluorescence indexes may show dissimilar sensitivity to monitor the removal of pharmaceuticals during AOPs in wastewater.

Hence, aims of this study were: (i) to investigate the removal of pharmaceuticals by a new AOP based on the combination of ozone, chlorine and UV ($Cl_2/O_3/UV$) in wastewater; (ii) to critically compare the removal of different pharmaceuticals by different ozone-based and UV-based AOPs (UV/H_2O_2 , UV/Cl_2 , O_3 , O_3/UV , $H_2O_2/O_3/UV$, $Cl_2/O_3/UV$) during wastewater treatment at pilot scale; (iii) to investigate the degradation and evolution of different fluorescing components of wastewater organic matter during diverse AOP treatments; (iv) to identify the most sensitive surrogate parameters based on fluorescence measurements suitable 1c.⁻ monitoring the removal of pharmaceuticals during different AOPs.

2. Materials and methods

2.1. Chemicals and reagents

All purchased solvents, standards, and reagen 's were of high purity. The details concerning these materials are reported in the Supplementary material section (Text S1). The selection of six pharmaceuticals (i.e., carbamazet ne - CBZ, fluoxetine - FLU, gemfibrozil - GMF, primidone - PRM, sulfamethoxazole - SMZ, 'rinnethoprim - TMP) as target CEC was based on data presented in previous literature that rely on chemical-physical properties, reaction rates with different oxidants, photosensitivity, or d availability of robust analytical methods (Anumol and Snyder, 2015; Gerrity et al., 2012; Guo et al., 2018; Lam et al., 2005; Wols et al., 2014; H. W. Yu et al., 2015). Particularly, target compounds were selected in order to investigate micro-pollutants, which show very different reactivity with the oxidants and radical species examined in this study. Detailed information about the selected pharmaceuticals is reported in Table 1.

2.2. AOPs pilot plant and experimental conditions

The container-based AOP pilot-scale plant, which has a capacity to treat a flow rate of 1000 – 6000 L per hour, was designed by Wedeco (Xylem, Germany) and installed on site at a WWTP treating municipal wastewater. The treatment train of the investigated WWTP foresees preliminary treatments followed by a biological nutrient removal oxidation ditch, which operates on an extended aeration, nitrification, and denitrification process within the oxidation ditch by cycling the aeration on and off. The clarified effluent is then sand filtered before its utilization as influent of the AOP pilot plant. Typical water quality parameters of the wartewater influent to the pilot plant are reported in Table 2. Concentrations of target pharmaccaticals in wastewater before AOP treatment are reported in Table 1.

The AOP pilot-scale system consisted of dosing pump for H_2O_2/Cl_2 addition, ozone generator, LP-UV-reactor with an intensity of radiant energy ranging from 65 to 75 W/m², and final degasser vessel for stripping ozone residual gas from the wastewater effluent. Several sampling points allow collection of the wastewater enorging the pilot system: after mixing of H_2O_2/Cl_2 in the main stream, after ozone dosage, and the final effluent of the pilot plant (Figure S1). UV doses for the wastewater treatment wore selected by changing the flowrate that passed through the LP-UV-reactor, which had a volume of 21 L. Tested ozone doses were 0.5, 1, 1.5, 3, 4.5, 6, 7.5, 9 mg O₃/L. Using these transferred ozone doses, an ozone residual in the range 0 – 1.2 mg/L was measured after ozone injection in the wastewater stream. Tested UV doses were 191 mJ/cm² (flow rate of 6000 L/h), 465 mJ/cm² (flow rate of 2500 L/h), and 981 mJ/cm² (flow rate of 1200 L/h). In this work, experiments were accomplished by different ozone and UV doses to evaluate the degradation kinetics of target pharmaceuticals. In addition, selected ozone and UV doses were typical for wastewater treatment (Lee et al., 2016). During AOP treatments, H₂O₂ and Cl₂ were added to the pilot influent at concentrations of 10 mg/L (i.e., 0.29 mM), and 3 mg/L (i.e.,

0.04 mM), respectively, which are typical doses used for wastewater treatment (Guo et al., 2018; Liu et al., 2019a; Miklos et al., 2019). In the case of chlorine, sodium hypochlorite solution was dosed in order to measure a total chlorine residual of 3 mg/L soon after the mixing with the wastewater stream. Investigated AOPs resulted by the combination of different oxidants and included UV/H₂O₂, UV/Cl₂, O₃, O₃/UV, H₂O₂/O₃/UV, Cl₂/O₃/UV. Experiments designed to compare UV-based AOPs (i.e., UV/H_2O_2 , UV/Cl_2) were performed at different UV doses. On the contrary, experiments designed to compare ozone-based AOPs (i., O₃, O₃/UV, H₂O₂/O₃/UV, $Cl_2/O_3/UV$) were accomplished varying the ozone doses, whereas the flow rate and, thus, the UV fluence was kept constant (i.e, fluence of 465 mJ/cm² with a flow rate of 2500 L/h). Lists of all AOP treatment conditions used to investigate fluorescing organic matter oxidation and pharmaceuticals removal are reported in Table S3 and Tat'e \$4, respectively. After reaction, which lasts few seconds in plug-flow rectors, residuation of idants (i.e., H₂O₂, Cl₂, O₃) were quenched by 10 mg/L of sodium bisulfite, which is an o. dant quenching agent that entails negligible effects on the optical properties of wastewater (reanic matter (Park and Snyder, 2018). While effluent samples were taken for each setting, different influent samples were taken during the experimentation time. However, no charges in water quality and pharmaceuticals concentrations in the wastewater influent to the pilot system were observed.

All samples were stored at 4 °C with ice packs upon collection and were brought to the laboratory. At the laboratory samples were immediately filtered, doped with the surrogate standards, and stored in fridge at 4 °C following the best preservation practices before pharmaceuticals analysis (Anumol and Snyder, 2015) and spectroscopic measurements (Sgroi et al., 2020a). Samples were stored in fridge one week for pharmaceuticals analysis, and two day for spectroscopic measurements.

2.3. Analytical methods

All pharmaceuticals were analyzed using an automated liquid chromatography online SPE system coupled to an Agilent 6460 triple-quadrupole mass spectrometer (Agilent Technologies, Santa Clara, CA). Further details of the analytical method are available in previously published literature (Anumol and Snyder, 2015), and are also briefly described in Supplementary material section (Text S2, Table S1 – S2). Resulting reporting limits in ultrapure water ranged from 0.1 to 3 ng/L (Table S5). For dissolved organic carbon (DOC) and to at classolved nitrogen (TN) concentrations analysis, samples were filtered through 0.45 μ m hydrophilic polypropylene filter (GHP Membrane Acrodisc, Pall Life Sciences) and acid the 1 to pH < 3 with hydrochloric acid. A Shimadzu TOC-L_{CSH} (Kyoto, Japan) total carbon analyzer was used for quantification.

Initial and residual concentrations of H_2O_2 we e determined on site at the AOP pilot-plant by the Peroxide Vacu-vials Kit (CHEMetrics) using a SAM photometer (V3000 SAM, CHEMetrics). Residual concentrations of free chlorine, total chlorine, and ozone were also determined on site using a portable Hach-Lange coeccophotometer (DR2500, Hach-Lange) and suitable reagent kits.

Absorbance measurement were performed with a Shimadzu UV-1800 spectrophotometer (Kyoto, Japan). Fluorescence data acquired by a Shimadzu RF-5301PC fluorescence spectrophotometer (Kyoto, Japan) were corrected as described in published work (Sgroi et al., 2020b) and also reported in Text S3. Fluorescence intensities were produced in Raman unit (RU). Parallel Factor (PARAFAC) analysis was carried out using the drEEM toolbox (Murphy et al., 2013) (details in Text S4).

2.4. Calculation of observed degradation rate constants

10

Values of observed degradation rate constants (k_{obs}) for pharmaceuticals and PARAFAC components were calculated using the pseudo-first order kinetic equation (Chen et al., 2017; Miklos et al., 2018a; von Sonntag and von Gunten, 2012). Particularly, for UV-based AOPs, it was used the equation:

$$\ln\left(\frac{c}{c_0}\right) = -k_{obs} \cdot fluence \quad (1)$$

where k_{obs} is in [cm²/mJ], and fluence in [mJ/cm²].

Calculation of k_{obs} values during ozone-based AOPs was ac complished by:

$$\ln\left(\frac{c}{c_0}\right) = -k_{obs} \cdot ozone \qquad (2)$$

where k_{obs} is in [L/mg], and the term "ozor 2" r present the transferred ozone dose in [mg/L].

3. Results and discussion

3.1. Removal of fluorescence and UV absorbance by different AOPs

In this study fluorescence spectra coupled with PARAFAC analysis, and UV absorbance measurements at 254 nm (UV₂,₄) were used to evaluate the reactivity of different radical species and oxidants with different DOM moieties, and, thus, the oxidation performance of different AOPs in wastewater. The simple visual analysis of fluorescence EEMs can provide a qualitative estimate of treatment efficacy of tested AOPs as shown in Figure 1 and Figure S2. Particularly, in Figure S2 the fluorescence EEM of the wastewater influent to the pilot plant is compared with EEMs of wastewater collected after addition of H_2O_2 and chlorine. In this case, no quenching agent was added to evaluate the full effect of H_2O_2/Cl_2 addition on fluorescence measurements. In Figure 1

are reported fluorescence EEMs obtained treating the tested wastewater by diverse AOPs. Different reduction of fluorescence intensities were produced by different AOPs. Particularly, it is easily observable that at same level of UV fluence, UV/Cl₂ process was more effective to degrade fluorescing organic matter than UV/H₂O₂ process. On the other hand, at same ozone dose and UV fluence, Cl₂/O₃/UV was the most effective process to degrade fluorescing organic matter between the ozone-based AOPs investigated in this study. O₃ and O₃/UV produced similar reduction of fluorescence intensities, which was lower than fluorescence reduction produced by the H₂O₂/O₃/UV process (Figure 1). Overall, ozone-based AOPs. In this study, removal of DOC, which is a further bulk parameter of water, was insignificant for all tested conditions confirming the negligible mineralization of wastewater organic matter organic matter organic matter von oxidation processes (von Sonntag and von Gunten, 2012).

A useful tool for EEMs interpretation is ^DARAFAC analysis. This method, which is a technique of multivariate data analysis, en bles the deconvolution of complex EEMs into independent components that represent grouns of similarly behaving fluorophores. Such deconvolution helps discriminate and ascertain contributions of different DOM types, and by providing the fluorescence maxima intensity *fer* the identified components it gives a basis for quantitative analysis of change in the composition of fluorescent organic matter during water treatment (Murphy et al., 2013; Sgroi et al., 2018b). In this study, PARAFAC analysis identified 4 independently varying fluorescing components as shown in Table 3, which reports the positions of the excitation and emission maxima for each component and the related fluorescence intensities observed in the wastewater before AOP treatment. The excitation and emission loadings of these fluorescent components, denoted henceforth as C1–C4, are shown in Figure S3. Figure S4 shows the corre-

sponding spectral fingerprints. Based on the position of the excitation and emission peaks, components C1, C2, and C3 were identified as humic- and fulvic-like fluorescence (Table 3 and Figure S2). Specifically, component C3 represents the contribution of a terrestrial fulvic- and humic-like component, and component C2 that of microbial humic-like fluorescence, as has been established in prior PARAFAC studies of surface water and wastewater (Sgroi et al., 2017b; H. Yu et al., 2015). Component C1 corresponds to a group of humic-like fluorescing species found in prior studies in high nutrient and wastewater impacted environments (Table 3). Tryptophanlike and proteinaceous fluorescing compounds are associated with components C4 (Table 3).

Degradation of different moieties of DOM was evalua ed by plotting the decline of normalized fluorescing PARAFAC components and UV_{254} with respect to ozone dose or fluence (Figure 2). Particularly, degradation of DOM was evaluated at different fluence exposures for the UV-based AOPs, whereas degradation of DOM by ozon-based AOPs was assessed at different ozone doses (Figure 2). Observed percentage removal for all tested AOP conditions are reported in Table S3.

Control experiments showed that UV irradiation alone or H_2O_2 addition alone did not change the optical properties of wall towater organic matter, whereas slight removal of UV₂₅₄ and fluorescing components (10 – 28%) were produced by chlorine addition (Table S3) in agreement with previous studies (Miklos et al., 2019; Sgroi et al., 2020a). During all tested AOP treatments, reduction of UV₂₅₄ and intensity of PARAFAC components increased with the increase of applied ozone dose/fluence (Figure 2). Particularly, observed removal of UV₂₅₄ and PARAFAC components was different between different AOPs. Indeed, different fluorescing DOM moieties showed different reactivity with radical species and oxidants produced during different AOPs. For an effective comparison of the oxidation performance among all tested AOPs, the natural logarithm of

the relative residual fluorescence intensity of each PARAFAC component or UV₂₅₄ value (C/C₀) was plotted as a function of UV-fluence or ozone dose (Figure S5). Linear regression lines were determined and the respective slopes, which represent the observed pseudo first-order degradation rate constants (k_{obs}), were obtained (Table 4) according to Eq. (1) and Eq. (2) (Chen et al., 2017; Miklos et al., 2019). For such regression analyses, data points related to the plateau of the normalized degradation curves (Figure 2) were excluded to avoid to skew values of the coefficient of determination (\mathbb{R}^2) and accomplish incorrect comparisons between the calculated k_{obs} (Figure S5).

Based on the obtained k_{obs} values (Table 4), the degrad atto 1 order of UV₂₅₄ and identified PAR-AFAC components was C4 > C1 > C2 > C3 > UV₂₅₄ for the UV-based AOPs (i.e., UV/H₂O₂, UV/Cl₂). On the contrary, the degradation order was C1 > C4 > C2 > C3 > UV₂₅₄ during the ozone-based AOPs (i.e., O₃, O₃/UV, Cl₂/O₃/UV), except for the H₂O₂/O₃/UV process, where the degradation order of UV₂₅₄ and PARATAC components was the same of the UV-based AOPs. This is the first study to compare the degradation of different PARAFAC components by different radical species under a broad selection of AOP treatments. Two previous studies performed a similar comparison for the O₃, UV/H₂O₂ and UV/persulfate processes, but such comparison was performed at bench-scale asing synthetic wastewater, which entailed the determination of diverse fluorescing PARAFAC components than those identified in this work (Ahn et al., 2017).

Oxidants and main radical species that should be produced during the investigated AOPs include ozone, 'OH, and RCS (i.e., Cl[•], Cl[•]₂, ClO[•]). Ozone is a selective oxidant, which has been suggested to react with aromatic and other electron-rich components of DOM by electron transfer reactions (von Sonntag and von Gunten, 2012). RCS are also selective oxidants, which react

preferentially with electron-rich moieties such as olefins, phenols, anilines, and alkyl-/alkoxybenzenes (Guo et al., 2018, 2017). On the contrary, 'OH radicals have been classified as non-selective oxidants able to react quickly with structurally very different compounds. Nevertheless, OH radicals are also electrophilic oxidants, and, thus, they tend to react faster with aromatic compounds compared to substances with electron-withdrawing moieties (Lee and Von Gunten, 2016; Westerhoff et al., 1999). All these discussed observations are in agreement with the observed degradation order of PARAFAC components in this work. Indeed, component C4, which is typical of aromatic and proteinaceous substances (Chora et al., 2003), was the most degraded or the second most degraded component in all tested AOPs. Component C1 was the most reduced fluorescence by O3, O3/UV and Cl2/O3/UV processes, and it was the second most degraded fluorescing component by all other $AO^{\mathbf{p}_{k}}$ C is a humic-like fluorescence component typical of wastewater environments. Hum. 2-a ids are a wide class of compounds, which include quinones, phenols, and carboxylic acids (De Melo et al., 2016). Hence, humic-like fluorescing substances also contain electron-rich or genic compounds able to react rapidly with selective oxidants, such as O₃ and RCS. Fur hernore, C1 was the component with the highest fluorescence intensity in the untreated waster (Table 3), and, probably, the most abundant group of independent fluorophores in the tested water if considering that this group of fluorophores is scarcely removed by biological treatments (Cohen et al., 2014; Sgroi et al., 2017a). The supposed high abundance of component C1 may have contributed to the observed degradation rates by various oxidants as well. Previous studies have shown that microbial derived DOM has lower aromaticity and reactivity with ozone than DOM obtained from other sources in natural waters (Westerhoff et al., 1999). This observation is in agreement with the observed lower k_{obs} values of the microbial component C2 compared to C4 and C1. Component C3 was the group of fluoro-

phores that showed the lowest reactivity with all oxidant species produced in this work. Component C3 is a terrestrial fulvic-like fluorescing component. Fulvic-acids are generally less aromatic and have a lower number of reaction sites than humic-acids (Senesi et al., 1989; Westerhoff et al., 1999). This fact may explain the observed low reactivity for component C3. Finally, previous studies have also hypothesized fluorescence DOM to be lower in molecular weight than UV-absorbing DOM (Sgroi et al., 2018a; Shimabuku et al., 2017; Velten et al., 2011). Particularly, studies that investigated the reactivity of different DOM fractions based on molecular weights (MW) and size exclusion chromatography bace shown that high MW DOM moieties (e.g., biopolymers) have low reactivity with oxidents (e.g., ozone) (Dong et al., 2010; von Sonntag and von Gunten, 2012). In addition, since the rescence is ascribed to an extended π electron system, the reaction of radicals/oxidants with fluorophore groups might reduce fluorescence signals, while chromophore challed ristics of the compound may still be present (Lakowicz, 2006). These rationales are n. agreement with the observed lower reduction of UV₂₅₄ compared to fluorescence by AOPs

When comparing the two UV- ι_2 sed AOPs (i.e., UV/H₂O₂, UV/Cl₂), it is easy to observe that all identified PARAFAC fluores ing components were better degraded during the UV/Cl₂ process. The higher oxidation performance of UV/Cl₂ compared to UV/H₂O₂ has already been described by previous studies that investigated the removal of micro-pollutants from water and wastewater, and it was related to the higher photolysis rate constants of chlorine compared to H₂O₂, which results in a very high yield of RCS (Fang et al., 2014; Guo et al., 2018, 2017; Miklos et al., 2019). Particularly, even though the used chlorine molar concentration (i.e., 0.04 mM) was lower than used H₂O₂ molar concentration (i.e., 0.29 mM), the chlorine consumption by UV photolysis was significantly higher (average consumed Cl₂ ~ 0.028 mM) than that of hydrogen peroxide (aver-

age consumed $H_2O_2 \sim 0.009$ mM) during the UV treatments investigated in this work. Furthermore, it has to be highlighted that the investigated wastewater was a fully nitrified tertiary effluent, where measurements of free chlorine concentration and total chlorine concentration were very similar. This fact confirms that the investigated UV/Cl₂ process worked as an actual UV/free chlorine process, and not as an UV/chloramine process, which has a lower oxidation performance (Wu et al., 2019; Zhang et al., 2019).

O₃ and O₃/UV processes showed very similar oxidation performance (Table 4 and Figure 2) in agreement with previous studies that reported limited increa e of 'OH production when combining ozone and UV in wastewater (Lado Ribeiro et al. 2019, Miklos et al., 2018b; H. Wang et al., 2018). On the contrary, $H_2O_2/O_3/UV$ and $Cl_2/O_3/UV$ and a better oxidation performance, even though the degradation order of PARATAC components was different for these two AOPs as previously discussed. Except component C4, the Cl₂/O₃/UV AOP outperformed the H₂O₂/O₃/UV process for the degradatio on all PARAFAC components. This fact can be probably related to the different radical species and yields of radicals produced in these two AOPs. Particularly, a significant production of 'OH is expected in $H_2O_2/O_3/UV$, whereas both 'OH and RCS are formed during he Cl₂/O₃/UV AOP. During the Cl₂/O₃/UV process, RCS can be produced by the UV photolysis of chorine (Guo et al., 2018), and during the reaction of chlorine with ozone (Huang et al., 2020). Although a slow reaction has been reported between hypochlorite and ozone (k = $170 \text{ M}^{-1} \text{ s}^{-1}$) (Haag and Hoigne, 1983; von Sonntag and von Gunten, 2012), RCS can be generated following the high reaction rate of HOCl/OCl⁻ with 'OH (k = 2.0 x $10^9 - 8.8 \times 10^9 \text{ M}^{-1} \text{ s}^{-1}$) (Fang et al., 2014; Guo et al., 2018). Further water constituents (e.g., bromide, carbonates, DOM components) may lead to the production of secondary radical species getting complex the chemistry of the process (Cheng et al., 2018; von Sonntag and von Gunten, 2012).

3.2. Removal of emerging contaminants by different AOPs

Photolytic removal of target pharmaceuticals is reported in Table S4, and it aligns well with experimental results obtained in previous studies (Guo et al., 2018; Miklos et al., 2019, 2018a). UV photolysis alone under the investigated conditions (i.e., fluence or '65 mJ/cm² and 981 mJ/cm²) produced a significant degradation of SMZ (52 - 75%), and a low removal of FLU and GMF (9 – 37%). On the contrary, the effect of UV photolysis was regugible on the removal of other investigated pharmaceuticals (i.e., TMP, PRM and CBZ). Plevious studies have also shown that degradation of pharmaceuticals is negligible by H₁C₂ alone, whereas the removal of some micropollutants, such as TMP and SMZ is significant to predict the pharmaceutical (100%) during control experiment, where chlorine removed very effectively SMZ (92%) and TMP (100%) during control experiment, where chlorine was allowed to react in wastewater until depletion (Table S4). The effect of chlorine in the removal of other pharmaceuticals was negligible (Table S4). It is interesting to observe that chlorin alone was more effective to remove SMZ and TMP than many investigated AO₁ vie., UV/H₂O₂, UV/Cl₂, O₃, O₃/UV) when operated at low ozone dose/fluence (Table S4).

Figure 3 shows normalized concentration of target pharmaceuticals as function of the employed ozone dose or fluence. Observed percentage removal of pharmaceuticals for all tested AOP conditions are reported in Table S4. Even in this case, for an effective comparison of the oxidation performance of target pharmaceuticals by different AOPs, the natural logarithm of the relative residual concentration (C/C_0) of each pharmaceutical was plotted as a function of UV-fluence or

ozone dose (Figure S6). Linear regression lines were determined and the respective slopes, which represent the observed pseudo first-order degradation rate constants (k_{obs}), were obtained according to Eq. (1) and Eq. (2) (Table 5). In some cases, calculation of k_{obs} values was not possible for some pharmaceutical, which were reduced at concentration level below the detection limit by the lowest used oxidant dosages. In Table 5, the contaminant degradation was labelled as "*very fast*" if the compound concentration was below the minimum reporting limit at the lowest oxidant dose, whereas it was labelled as "*fast*" if the compound concentration was below the minimum reporting limit at the second lowest oxidant dose.

By the analysis of Figure 3 and the size of box plots in Tayle 5, it is observable that radical species produced in the UV/Cl₂ process (i.e., RCS and 'GH) showed higher selectivity than radicals formed by UV/H₂O₂ (i.e., 'OH) for the reaction with pharmaceuticals. Particularly, the higher selectivity of RCS compared to hydroxyl radicals resulted in a higher range of k_{obs} values (difference between maximum and minimum value, i.e. Δk_{obs}) in the UV/Cl₂ process than in the UV/H₂O₂ AOP (see box plots in ⁴ able 5). On the contrary, such selectivity of RCS was not evident for the degradation of PArArAC components (Figure 2 and Table 4) suggesting that most of fluorescing organic n atte constituents in wastewater are electron-rich moieties with high propensity to react with 'ACS. Outcomes of the experiments showed that UV/Cl₂ process outcompeted UV/H₂O₂ for the removal of the antibiotics TMP and SMZ, whereas UV/H₂O₂ was superior in the degradation of PRM, CBZ and GMF. The two processes showed similar effectiveness to remove FLU.

When comparing the ozone-based AOPs, the effectiveness in the degradation of pharmaceuticals was in the order $H_2O_2/O_3/UV > O_3/UV > O_3$ if excluding $Cl_2/O_3/UV$ (Table 5). As expected, the size of the box plots in Table 5 was similar for these three AOPs, since same radical species (i.e.,

'OH) were produced. On the contrary, a very high compound selectivity for the oxidation of pharmaceuticals was observed during the Cl₂/O₃/UV AOP (Table 5). Particularly, Cl₂/O₃/UV was the most effective process to degrade SMZ, CBZ and GMF. A similar effectiveness (i.e., slightly lower) to H₂O₂/O₃/UV for this new ozone and chlorine-based AOP was observed for the removal of FLU, whereas the removal of PRM was very low, and it was lower than simple ozonation (Table 5 and Table S4). PRM has a low reactivity with ozone and RCS, whereas it can be effectively oxidized by 'OH (Table 1). Nevertheless, the presence of chlorine (i.e., HOCl/OCl⁻) in the Cl₂/O₃/UV process is able to significantly scavenges 'O^{III} ($\therefore = 2.0 \times 10^9 - 8.8 \times 10^9 \text{ M}^{-1} \text{ s}^{-1}$) (Fang et al., 2014; Guo et al., 2018) reducing the capability of this AOP to degrade PRM. Finally, TMP was very quickly removed by all investigated 'OPs except UV/H₂O₂.

To sum up, differences can be observed when comparing different AOPs in terms of change of fluorescing organic matter or pharmaceutical degradation. Overall, chlorine-based AOPs were the most effective processes to degrade there is components in wastewater when compared to similar AOPs that used H_2O_2 instead of chlorine. On the contrary, the effectiveness of different AOPs in the removal of pharma ceuticals was compound-specific because of the different selectivity of formed radical species with target pharmaceutical. Finally, it can be highlighted that the new $Cl_2/O_3/UV$ process v as the most effective AOP to degrade fluorescing organic matter and all investigated pharmaceuticals except PRM.

3.3. Sensitivity of surrogate parameters for on-line monitoring

The analysis of pharmaceuticals at trace levels in water is laborious, time-consuming and expensive. In addition, it requires sophisticated analytical equipment and highly trained technicians. Hence, the use of surrogate parameters that can accurately predict the removal of pharmaceuti-

cals in a simple, fast, and cost-effective manner is highly desirable. In the last decade, the use of spectroscopic parameters like UV absorbance and fluorescence has been shown to be a promising approach in predicting the removal of pharmaceuticals during various AOP treatments (Gerrity et al., 2012; Miklos et al., 2019; Park et al., 2017; H. W. Yu et al., 2015). Therefore, the existing literature offers the following conclusions: (1) spectroscopic parameters based on UV and fluorescence measurements are strongly correlated with the elimination of aromatic and nonaromatic pharmaceuticals, (2) each compound has a unique set of regression parameters related to its rate constants for reactions with various oxidants, (3) main processes with different oxidation mechanisms (e.g., ozone/UV vs. UV/H₂O₂) also have unique sets of correlations, and (4) the correlations for specific contaminants and oxidation processes are consistent between different secondary or tertiary effluents (Gerrity et al., 2017; Korshin et al., 2018; Miklos et al., 2019). Furthermore, in this study we observed th. t d' ferent fluorescing organic matter components and UV254 have different reaction rates with *lifterent oxidant/radical species*. In Table 6 are reported the calculated regression parameters of linear correlations between the removals of pharmaceuticals and the removal of different spectroscopic indexes, which included UV₂₅₄ and PARAFAC components. Particularly, regulation parameters shown in Table 6 resulted unique for each compound, surrogate parame. r and oxidation process. The calculated coefficients of determination (R^2) for those correlations are reported in Table S6.

Surrogate parameters that have high slope of regression line are inconvenient indexes for realtime monitoring of pharmaceuticals. Indeed, these indexes indicate high pharmaceuticals removal per unit % change of their value. On the contrary, the most sensitive surrogate parameter to monitor pharmaceuticals oxidation is the spectroscopic index with the lowest slope in the regression line. In this case, unit % change of the spectroscopic parameter is able to quantify small re-

moval of pharmaceuticals. As an example, in Figure 4 is highlighted the different sensitivity of UV_{254} and PARAFAC component C4 to monitor the removal of PRM during the UV/H_2O_2 treatment. In Table 6 are highlighted the most sensitive spectroscopic surrogates to monitor pharmaceuticals upon the investigated AOPs. The most suitable index for monitoring the removal of pharmaceuticals was different for each investigated AOP. Particularly, component C4 resulted the preferable index to monitor UV/H_2O_2 , O_3 , O_3/UV , and $Cl_2/O_3/UV$ AOPs, component C1 was the best surrogate to monitor UV/Cl_2 process, whereas corror Oral C3 was the most suitable parameter to monitor $H_2O_2/O_3/UV$ treatment. This found is in agreement with the diversity of radical species that can be produced during different ACPs, and that show different reactivity with diverse organic matter components. Finally, it can be abserved that fluorescence indexes were more sensitive measurements than UV_{254} to not it pharmaceuticals oxidation by various AOPs.

4. Conclusions

This study investigated the rem. val of fluorescing organic matter and selected pharmaceuticals (i.e., CBZ, FLU, GMF, PRM, CMZ, TMT) from wastewater by different UV- and ozone-based AOPs (i.e., UV/H₂O₂, U^{*}/Cl_2 , O₃, O₃/UV, H₂O₂/O₃/UV, Cl₂/O₃/UV) at pilot-scale. In addition, this study evaluated the sensitivity of different spectroscopic parameters based on UV and fluorescence measurements to predict pharmaceuticals removal. Based on the results of the study, the following conclusions can be obtained:

Radical species generated during chlorine-based AOPs (i.e., UV/Cl₂, Cl₂/O₃/UV) showed higher selectivity than those generated by H₂O₂- and ozone-based AOPs (i.e., UV/H₂O₂, O₃, O₃/UV, H₂O₂/O₃/UV) for the reaction with different pharmaceuticals. On

the contrary, such high selectivity of radical species produced by chlorine-based AOPs was not observed during the reaction with fluorescing components of wastewater organic matter;

- Tryptophan-like substances and humic-like fluorescing compounds typical of wastewater environments were the most degraded fluorescing components by all AOPs, whereas microbial products and fulvic-like fluorescing substances resulted less reactive to oxidation. Low removal of UV absorbance at 254 nm vere observed by all investigated AOPs. Overall, chlorine-based AOPs were more effective to reduce fluorescence intensities than H₂O₂-based AOPs;
- The new proposed Cl₂/O₃/UV process was the new seffective AOP to degrade all investigated pharmaceuticals except PRM, which had a very low removal. When comparing other ozone-based AOPs, the oxide ion performance of pharmaceuticals followed the order H₂O₂/O₃/UV > O₃/UV > O₂. UV/Cl₂ process (Cl₂ = 3mg/L) showed better removal of TMP and SMZ, similar worked of FLU, and lower removal of PRM, CBZ and GMF than UV/H₂O₂ AOP (H₂O₂ = 10 mg/L);
- Correlations between the removal of pharmaceuticals and the removal of spectroscopic indexes (i.e., PARAFAC components and UV₂₅₄) had unique regression parameters for each compound, surrogate parameter and oxidation process. This fact entails a different sensitivity for monitoring pharmaceuticals by different surrogate parameters since the slope of regression line affects the extent of change of pharmaceuticals removal that can be monitored per unit % change of fluorescence intensity. Particularly, component C4 (i.e., tryptophan-like fluorescence) resulted the preferable index to monitor pharmaceuticals removal by UV/H₂O₂, O₃, O₃/UV, and Cl₂/O₃/UV AOPs. Component C1

(humic-like fluorescence) was the best surrogate to monitor UV/Cl_2 process, whereas component C3 (fulvic-like fluorescence) was the most suitable parameter to monitor pharmaceuticals oxidation by $H_2O_2/O_3/UV$ treatment.

Supplementary data

Texts S1 - S4, Table S1 - S6, and Figures S1 - S6. This material is available free of charge.

Acknowledgements

This study was partially funded by the University of Catame within the "Piano di incentivi per la Ricerca di Ateneo 2020/2022" of the Department of C²vil Engineering and Architecture, Project "Materiali e Metodologie chimico-fisiche avanta per l'abbattimento di contaminanti Xenobiotici (MaMeX)". Authors are grateful to V. ed. co (Xylem, Germany) for the equipment and technical support used in this study.

References

- Ahn, Y., Lee, D., Kwon, M., Choi, I. hwan, Nam, S.N., Kang, J.W., 2017. Characteristics and fate of natural organic matter during UV oxidation processes. Chemosphere 184, 960– 968. doi:10.1016/j.chemosphere.2017.06.079
- Anumol, T., Snyder, S.A., 2015. Rapid analysis of trace organic compounds in water by automated online solid-phase extraction coupled to liquid chromatography-tandem mass spectrometry. Talanta 132, 77–86. doi:10.1016/j.talanta.2014.08.011
- Benotti, M.J., Trenholm, R.A., Vanderford, B.J., Holady, J.C., Stanford, B.D., Snyder, S.A., 2009. Pharmaceuticals and endocrine disrupting compounds in U.S. drinking water. Environ. Sci. Technol. 43, 597–603. doi:10.1021/es8018452
- Carstea, E.M., Bridgeman, J., Baker, A., Reynolds, D.M., 2016. F uorescence spectroscopy for wastewater monitoring: A review. Water Res. 95, 205–219. doi:10.1016/j.watres.2016.03.021
- Cerreta, G., Roccamante, M.A., Plaza-bolanos, P., Olter, J., Aguera, A., Malato, S., Rizzo, L., 2020. Advanced treatment of urban wastewater by JV-C/free chlorine process : Micro-pollutants removal and effect of UV-C radiation on trihalomethanes formation. Water Res. 169, 115220. doi:10.1016/j.watres.2010.115220
- Chen, W., Westerhoff, P., Leenheer, J.A., Booksn, K., 2003. Fluorescence Excitation-Emission Matrix Regional Integration. 9 Quantify Spectra for Dissolved Organic Matter. Environ. Sci. Technol. 37, 5701-5710. doi:10.1021/es034354c
- Chen, Z., Li, M., Wen, Q., Ren, N., 2(1). Evolution of molecular weight and fluorescence of effluent organic matter (EfC M, during oxidation processes revealed by advanced spectrographic and chrom tographic tools. Water Res. 124, 566–575. doi:10.1016/j.watres.2017.09006
- Cheng, S., Zhang, X., Yeng, X., Shang, C., Song, W., Fang, J., Pan, Y., 2018. The Multiple Role of Bromide Jo. in . PCPs Degradation under UV/Chlorine Treatment. Environ. Sci. Technol. 52, 1806–1816. doi:10.1021/acs.est.7b03268
- Cohen, E., Levy, G.J., Borisover, M., 2014. Fluorescent components of organic matter in wastewater: Efficacy and selectivity of the water treatment. Water Res. 55, 323–334. doi:10.1016/j.watres.2014.02.040
- Cruz-Alcalde, A., Esplugas, S., Sans, C., 2019. Abatement of ozone-recalcitrant micropollutants during municipal wastewater ozonation: Kinetic modelling and surrogate-based control strategies. Chem. Eng. J. 360, 1092–1100. doi:10.1016/j.cej.2018.10.206
- Daughton, C.G., Ternes, T.A., 2009. Pharmaceuticals and Personal Care Products in the Environment: Agents of subtle change? Environ. Health Perspect. 107, 907–938. doi:10.1021/bk-2001-0791

De Melo, B.A.G., Motta, F.L., Santana, M.H.A., 2016. Humic acids: Structural properties

and multiple functionalities for novel technological developments. Mater. Sci. Eng. C 62, 967–974. doi:10.1016/j.msec.2015.12.001

- Dickenson, E.R.V., Snyder, S.A., Sedlak, D.L., Drewes, J.E., 2011. Indicator compounds for assessment of wastewater effluent contributions to flow and water quality. Water Res. 45, 1199–1212. doi:10.1016/j.watres.2010.11.012
- Dong, M.M., Mezyk, S.P., Rosario-Ortiz, F.L., 2010. Reactivity of effluent organic matter (EfOM) with hydroxyl radical as a function of molecular weight. Environ. Sci. Technol. 44, 5714–5720. doi:10.1021/es1004736
- Fang, J., Fu, Y., Shang, C., 2014. The roles of reactive species in micropollutant degradation in the UV/free chlorine system. Environ. Sci. Technol. 48, 1859–1868. doi:10.1021/es4036094
- Focazio, M.J., Kolpin, D.W., Barnes, K.K., Furlong, E.T., Me yer, M.T., Zaugg, S.D., Barber, L.B., Thurman, M.E., 2008. A national reconnaissance for plarmaceuticals and other organic wastewater contaminants in the United States - II Untreated drinking water sources. Sci. Total Environ. 402, 201–216. doi:10.1016/j.scitotenv.2008.02.021
- Gerrity, D., Gamage, S., Jones, D., Korshin, G. V., Lev V., Pisarenko, A., Trenholm, R.A., von Gunten, U., Wert, E.C., Snyder, S.A., 2012. Development of surrogate correlation models to predict trace organic contaminar (cx) lation and microbial inactivation during ozonation. Water Res. 46, 6257–6272. dc::10.1016/j.watres.2012.08.037
- Gogate, P.R., Pandit, A.B., 2004. A review of imperative technologies for wastewater treatment II: Hybrid methods. Adv. Environ. Res. 8, 553–597. doi:10.1016/S1093-0191(03)00031-5
- Guillossou, R., Le Roux, J., Brosillon, S., Mailler, R., Vulliet, E., Morlay, C., Nauleau, F., Rocher, V., Gaspéri, J., 202: Benefits of ozonation before activated carbon adsorption for the removal of organic micropollutants from wastewater effluents. Chemosphere 245, 125530. doi:10.1016/j.chemosphere.2019.125530
- Guo, K., Wu, Z., Shang, C., 'ao, B., Hou, S., Yang, X., Song, W., Fang, J., 2017. Radical Chemistry and Structural Relationships of PPCP Degradation by UV/Chlorine Treatment in Simula ed Drinking Water. Environ. Sci. Technol. 51, 10431–10439. doi:10.1021/acs.est.7b02059
- Guo, K., Wu, Z., Yan, S., Yao, B., Song, W., Hua, Z., Zhang, X., Kong, X., Li, X., Fang, J., 2018. Comparison of the UV/chlorine and UV/H2O2 processes in the degradation of PPCPs in simulated drinking water and wastewater: Kinetics, radical mechanism and energy requirements. Water Res. 147, 184–194. doi:10.1016/j.watres.2018.08.048
- Haag, W.R., Hoigne, J., 1983. Ozonation of Water Containing Chlorine or Chloramines: Reaction Products and Kinetics. Water Res. 17, 1397–1983. doi:doi:10.1016/0043-1354(83)90270-1
- Huang, N., Wang, W.L., Xu, Z. Bin, Lee, M.Y., Wu, Q.Y., Hu, H.Y., 2020. A study of synergistic oxidation between ozone and chlorine on benzalkonium chloride degradation: Reactive species and degradation pathway. Chem. Eng. J. 382, 122856. doi:10.1016/j.cej.2019.122856

- Korshin, G. V., Sgroi, M., Ratnaweera, H., 2018. Spectroscopic surrogates for real time monitoring of water quality in wastewater treatment and water reuse. Curr. Opin. Environ. Sci. Heal. 2, 12–19. doi:10.1016/j.coesh.2017.11.003
- Lado Ribeiro, A.R., Moreira, N.F.F., Li Puma, G., Silva, A.M.T., 2019. Impact of water matrix on the removal of micropollutants by advanced oxidation technologies. Chem. Eng. J. 363, 155–173. doi:10.1016/j.cej.2019.01.080

Lakowicz, J.R., 2006. Principles of fluorescence spectroscopy, 3rd ed. Springer-Verlag.

- Lam, M.W., Young, C.J., Mabury, S.A., 2005. Aqueous photochemical reaction kinetics and transformations of fluoxetine. Environ. Sci. Technol. 39, 513–522. doi:10.1021/es0494757
- Lee, Y., Gerrity, D., Lee, M., Gamage, S., Pisarenko, A., Trenholm, R.A., Canonica, S., Snyder, S.A., Von Gunten, U., 2016. Organic Contaminant 2 batement in Reclaimed Water by UV/H2O2 and a Combined Process Consisting of 33/H2O2 Followed by UV/H2O2: Prediction of Abatement Efficiency, Energy Consumption, and Byproduct Formation. Environ. Sci. Technol. 50, 3809–3819. Voi:10.1021/acs.est.5b04904
- Lee, Y., Von Gunten, U., 2016. Advances in predicting organic contaminant abatement during ozonation of municipal wastewater effluent: Reaction kinetics, transformation products, and changes of biological effects Faviron. Sci. Water Res. Technol. 2, 421–442. doi:10.1039/c6ew00025h
- Lei, Y., Cheng, S., Luo, N., Yang, X., Ah, ^T., 2019. Rate constants and mechanisms of the reactions of Cl• and Cl2•- with Trace Organic Contaminants. Environ. Sci. Technol. doi:10.1021/acs.est.9b02462
- Liu, Z., Chys, M., Yang, Y., Demostere, K., Van Hulle, S., 2019a. Oxidation of Trace Organic Contaminants (TrC 's) in Wastewater Effluent with Different Ozone-Based AOPs: Comparison of Ozone Exposure and •OH Formation. Ind. Eng. Chem. Res. 58, 8896–8902. doi:10.1021/acs.iecr.9b00293
- Liu, Z., Hosseinzadeh, S., W. rdenier, N., Verheust, Y., Chys, M., Hulle, S. Van, 2019b. Combining ozone vitu UV and H2O2 for the degradation of micropollutants from different origins: lab scale analysis and optimization. Environ. Technol. (United Kingdom) 40, 3773–3782. doi:10.1080/09593330.2018.1491630
- Magdeburg, A., Stalter, D., Schlüsener, M., Ternes, T., Oehlmann, J., 2014. Evaluating the efficiency of advanced wastewater treatment: Target analysis of organic contaminants and (geno-)toxicity assessment tell a different story. Water Research, 50, pp. 35-47.
- Mehrjouei, M., Müller, S., Möller, D., 2015. A review on photocatalytic ozonation used for the treatment of water and wastewater. Chem. Eng. J. 263, 209–219. doi:10.1016/j.cej.2014.10.112
- Merel, S., Anumol, T., Park, M., Snyder, S.A., 2015. Application of surrogates, indicators, and high-resolution mass spectrometry to evaluate the efficacy of UV processes for attenuation of emerging contaminants in water. J. Hazard. Mater. 282, 75–85. doi:10.1016/j.jhazmat.2014.09.008

- Michael, I., Rizzo, L., McArdell, C.S., Manaia, C.M., Merlin, C., Schwartz, T., Dagot, C., Fatta-Kassinos, D., 2013. Urban wastewater treatment plants as hotspots for the release of antibiotics in the environment: A review. Water Res. 47, 957–995. doi:10.1016/j.watres.2012.11.027
- Miklos, D.B., Hartl, R., Michel, P., Linden, K.G., Drewes, J.E., Hübner, U., 2018a. UV/H2O2 process stability and pilot-scale validation for trace organic chemical removal from wastewater treatment plant effluents. Water Res. 136, 169–179. doi:10.1016/j.watres.2018.02.044
- Miklos, D.B., Remy, C., Jekel, M., Linden, K.G., Drewes, J.E., Hübner, U., 2018b. Evaluation of advanced oxidation processes for water and wastewater treatment – A critical review. Water Res. 139, 118–131. doi:10.1016/j.watres.2018.03.042
- Miklos, D.B., Wang, W.L., Linden, K.G., Drewes, J.E., Hübner, U., 2019. Comparison of UV-AOPs (UV/H2O2, UV/PDS and UV/Chlorine) for TOrC removal from municipal wastewater effluent and optical surrogate model evaluation. Chem. Eng. J. 362, 537– 547. doi:10.1016/j.cej.2019.01.041
- Murphy, K.R., Butler, K.D., Spencer, R.G.M., Stedmon, C. a, Boehme, J.R., Aiken, G.R., 2010. Measurement of Dissolved Organic Matter Eluorescence in Aquatic Environments: An Interlaboratory Comparison. Environ. Sci. Technol. 44, 9405–9412. doi:10.1021/es102362t
- Murphy, K.R., Hambly, A., Singh, S., Henderson, R.K., Baker, A., Stuetz, R., Khan, S.J., 2011. Organic matter fluorescence in Funicipal water recycling schemes: Toward a unified PARAFAC model. Environ. Sci. Technol. 45, 2909–2916. doi:10.1021/es103015e
- Murphy, K.R., Stedmon, C.A., Gracher, D., Bro, R., 2013. Fluorescence spectroscopy and multi-way techniques. PAR. FAC. Anal. Methods 5, 6557. doi:10.1039/c3ay41160e
- Park, M., Anumol, T., Daniels, Y.D., Wu, S., Ziska, A.D., Snyder, S.A., 2017. Predicting trace organic compound attenuation by ozone oxidation: Development of indicator and surrogate models. V ater Res. 119, 21–32. doi:10.1016/j.watres.2017.04.024
- Park, M., Snyder, S.A., 2/18. Sample handling and data processing for fluorescent excitationemission matrix (EEM) of dissolved organic matter (DOM). Chemosphere 193, 530– 537. doi:10.1016/j.chemosphere.2017.11.069
- Richardson, S.D., Ternes, T.A., 2018. Water Analysis: Emerging Contaminants and Current Issues. Anal. Chem. 90, 398–428. doi:10.1021/acs.analchem.7b04577
- Rizzo, L., Malato, S., Antakyali, D., Beretsou, V.G., Đolić, M.B., Gernjak, W., Heath, E., Ivancev-Tumbas, I., Karaolia, P., Lado Ribeiro, A.R., Mascolo, G., McArdell, C.S., Schaar, H., Silva, A.M.T., Fatta-Kassinos, D., 2019. Consolidated vs new advanced treatment methods for the removal of contaminants of emerging concern from urban wastewater. Sci. Total Environ. 655, 986–1008. doi:10.1016/j.scitotenv.2018.11.265
- Roccaro, P., Sgroi, M., Vagliasindi, F.G.A., 2013. Removal of xenobiotic compounds from wastewater for environment protection: Treatment processes and costs. Chem. Eng. Trans. 32, 505–510.

- Roccaro, P., 2018. Treatment processes for municipal wastewater reclamation: The challenges of emerging contaminants and direct potable reuse, Current Opinion in Environmental Science & Health, 2:46-54.
- Senesi, N., Miano, T.M., Provenzano, M.R., Brunetti, G., 1989. Spectroscopic and compositional comparative characterization of I.H.S.S. reference and standard fulvic and humic acids of various origin. Sci. Total Environ. 81–82, 143–156. doi:10.1016/0048-9697(89)90120-4
- Sgroi, M., Anumol, T., Roccaro, P., Vagliasindi, F.G.A., Snyder, S.A., 2018a. Modeling emerging contaminants breakthrough in packed bed adsorption columns by UV absorbance and fluorescing components of dissolved organic matter. Water Res. 145, 667–677. doi:10.1016/j.watres.2018.09.018
- Sgroi, M., Gagliano, E., Vagliasindi, F.G.A., Roccaro, P., 2020a. Absorbance and EEM fluorescence of wastewater: effects of filters, storage cor dity ns, and chlorination. Chemosphere 243, 125292. doi:https://doi.org/10.1016/j.chemosphere.2019.125292
- Sgroi, M., Gagliano, E., Vagliasindi, F.G.A., Roccaro, F. 2020b. Inner filter effect, suspended solids and nitrite/nitrate interferences in Juorescence measurements of wastewater organic matter. Sci. Total Environ. 711 134663. doi:https://doi.org/10.1016/j.scitotenv.2019.134663
- Sgroi, M., Pelissari, C., Roccaro, P., Sezerino, P.H., García, J., Vagliasindi, F.G.A., Ávila, C., 2018b. Removal of organic carbon, 'atr-gen, emerging contaminants and fluorescence organic matter in different constructe¹ wetland configurations. Chem. Eng. J. 332, 619–627. doi:https://doi.org/10.1016/j cej.2017.09.122
- Sgroi, M., Roccaro, P., Korshin, G. V., Creco, V., Sciuto, S., Anumol, T., Snyder, S.A., Vagliasindi, F.G.A., 2017a. Use of fluorescence EEM to monitor the removal of emerging contaminants in full scale wastewater treatment plants. J. Hazard. Mater. 323, 367–376. doi:10.1016/j.jha.mat.2016.05.035
- Sgroi, M., Roccaro, P., Korshin, G. V., Vagliasindi, F.G.A., 2017b. Monitoring the Behavior of Emerging Contaminants in Wastewater-Impacted Rivers Based on the Use of Fluorescence Excutation Emission Matrixes (EEM). Environ. Sci. Technol. 51, 4306– 4316. doi:10.1021/2.s.est.6b05785
- Shimabuku, K.K., Kennedy, A.M., Mulhern, R.E., Summers, R.S., 2017. Evaluating Activated Carbon Adsorption of Dissolved Organic Matter and Micropollutants Using Fluorescence Spectroscopy. Environmantal Sci. Technol. 51, 2676–2684.
- Varanasi, L., Coscarelli, E., Khaksari, M., Mazzoleni, L.R., Minakata, D., 2018. Transformations of dissolved organic matter induced by UV photolysis, Hydroxyl radicals, chlorine radicals, and sulfate radicals in aqueous-phase UV-Based advanced oxidation processes. Water Res. 135, 22–30. doi:10.1016/j.watres.2018.02.015
- Velten, S., Knappe, D.R.U., Traber, J., Kaiser, H.-P., von Gunten, U., Boller, M., Meylan, S., 2011. Characterization of natural organic matter adsorption in granular activated carbon adsorbers. Water Res. 45, 3951–3959. doi:10.1016/j.watres.2011.04.047

Villarín, M.C., Merel, S., 2020. Paradigm shifts and current challenges in wastewater

management. J. Hazard. Mater. 390, 122139. doi:10.1016/j.jhazmat.2020.122139

- Von Gunten, U., Oliveras, Y., 1998. Advanced oxidation of bromide-containig waters: Bromate formation mechanisms. Environ. Sci. Technol. 32, 63–70. doi:10.1021/es970477j
- von Sonntag, C., von Gunten, U., 2012. Chemistry of ozone in water and wastewater treatment: From Basic Principles to Applications, IWA Publis. ed.
- Wang, H., Zhan, J., Yao, W., Wang, B., Deng, S., Huang, J., Yu, G., Wang, Y., 2018. Comparison of pharmaceutical abatement in various water matrices by conventional ozonation, peroxone (O3/H2O2), and an electro-peroxone process. Water Res. 130, 127–138. doi:10.1016/j.watres.2017.11.054
- Wang, J., Zhuan, R., 2020. Degradation of antibiotics by advance¹ oxidation processes: An overview. Sci. Total Environ. 701, 135023. doi:10.1016/j.sci.otenv.2019.135023
- Wang, W.L., Wu, Q.Y., Huang, N., Xu, Z. Bin, Lee, M.Y. Hu H.Y., 2018. Potential risks from UV/H2O2 oxidation and UV photocatalysis: review of toxic, assimilable, and sensory-unpleasant transformation products. Water Res. 141, 109–125. doi:10.1016/j.watres.2018.05.005
- Wenk, J., Aeschbacher, M., Salhi, E., Canonica, S, Von Gunten, U., Sander, M., 2013. Chemical oxidation of dissolved organic nature by chlorine dioxide, chlorine, and ozone: Effects on its optical and anti-oxi land properties. Environ. Sci. Technol. 47, 11147–11156. doi:10.1021/es40251Cb
- Westerhoff, P., Aiken, G., Amy, G., Decroux, J., 1999. Relationships between the structure of natural organic matter and it, recruivity towards molecular ozone and hydroxyl radicals. Water Res. 33, 2265 2275. doi:10.1016/S0043-1354(98)00447-3
- Westerhoff, P., Mezyk, S.P., Coper, W.J., Minakata, D., 2007. Electron pulse radiolysis determination of hydroxyl radical rate constants with Suwannee river fulvic acid and other dissolved organic acter isolates. Environ. Sci. Technol. 41, 4640–4646. doi:10.1021/es0625.29n
- Wols, B.A., Harmsen, D. H., Beerendonk, E.F., Hofman-Caris, C.H.M., 2014. Predicting pharmaceutical degradation by UV (LP)/H2O2 processes: A kinetic model. Chem. Eng. J. 255, 334–343. doi:10.1016/j.cej.2014.05.088
- Wu, Y., Zhu, S., Zhang, W., Bu, L., Zhou, S., 2019. Comparison of diatrizoate degradation by UV/chlorine and UV/chloramine processes: Kinetic mechanisms and iodinated disinfection byproducts formation. Chem. Eng. J. 375, 121972. doi:10.1016/j.cej.2019.121972
- Yao, W., Ur Rehman, S.W., Wang, H., Yang, H., Yu, G., Wang, Y., 2018. Pilot-scale evaluation of micropollutant abatements by conventional ozonation, UV/O3, and an electro-peroxone process. Water Res. 138, 106–117. doi:10.1016/j.watres.2018.03.044
- Yu, H., He, P.J., Shao, M., 2010. Novel insights into sludge dewaterability by fluorescence excitation-emission matrix combined with parallel factor analysis. Water Res. 44, 797– 806.

- Yu, H., Liang, H., Qu, F., Han, Z., Shao, S., Chang, H., Li, G., 2015. Impact of dataset diversity on accuracy and sensitivity of parallel factor analysis model of dissolved organic matter fluorescence excitation-emission matrix. Sci. Rep. 5, 10207. doi:10.1038/srep10207
- Yu, H.W., Anumol, T., Park, M., Pepper, I., Scheideler, J., Snyder, S.A., 2015. On-line sensor monitoring for chemical contaminant attenuation during UV/H2O2 advanced oxidation process. Water Res. 81, 250–260. doi:10.1016/j.watres.2015.05.064
- Zhang, Z., Chuang, Y.H., Szczuka, A., Ishida, K.P., Roback, S., Plumlee, M.H., Mitch, W.A., 2019. Pilot-scale evaluation of oxidant speciation, 1,4-dioxane degradation and disinfection byproduct formation during UV/hydrogen peroxide, UV/free chlorine and UV/chloramines advanced oxidation process treatment for potable reuse. Water Res. 164, 114939. doi:10.1016/j.watres.2019.114939
- Zheng, M., Daniels, K.D., Park, M., Nienhauser, A.B., Cleverger, E.C., Li, Y., Snyder, S.A., 2019. Attenuation of pharmaceutically active compourds in aqueous solution by UV/CaO2 process: Influencing factors, degradation n ech mism and pathways. Water Res. 164, 114922. doi:10.1016/j.watres.2019.11492.

31

Figure 1. Fluorescence EEMs (RU) of the final effluent of the pilot plant after different AOPs treatments. Chlorine (Cl_2) was dosed at 3 mg/L, hydrogen peroxide (H_2O_2) at 10 mg/L.

Figure 2. Decline of normalized fluorescing PARAFAC components and UV absorbance at 254 nm (UV_{254}) with respect to fluence exposure or ozone dose for all investigated AOPs. Chlorine (Cl_2) was dosed at 3 mg/L, hydrogen peroxide (H_2O_2) at 10 mg/L. The UV fluence during the ozone based AOPs was 465 mJ/cm².

Figure 3. Decline of normalized concentration of targ. $^{+}$ pharmaceuticals with respect to fluence exposure or ozone dose for all investigated \therefore OPs. Chlorine (Cl_2) was dosed at 3 mg/L, hydrogen peroxide (H_2O_2) at 10 mg/L Γ Le UV fluence during the ozone based AOPs was 465 mJ/cm².

Figure 4. Difference in sensitivity between the PARAFAC component C4 and UV absorbance at 254 nm (UV₂₅₄) for monoring PRM during the UV/H₂O₂ treatment.

Table 1. Summary of target compounds with indication of their concentration before treatment, second-order rate constants with different radical species, quantum yield of photo-degradation at 254 nm (Φ_{254}), and molar absorption coefficient at 254 nm (ϵ_{254}).

	Concentration	k _{O3}			Φ_{254}	£254					
Compound	before treat-	(M ⁻¹ s ⁻¹),	к. _{ОН}		(10 ⁻² ,	(10 ³ ,	Reference				
	ment (ng/L)	pH = 7	$(\mathbf{M}^{-}\mathbf{S}^{-})$	$(\mathbf{M}^{-}\mathbf{S}^{-})$	mol/E)	L/M/cm)					
Group I – High reactivity with ozone and RCS. High photosensitivity.											
							(Gerrity et al.,				
		6	0	< 2.23 x			2012; Guo et				
SMZ	1813	3 x 10°	6 x 10²	10 ⁹	0.1	13	al., 2018; Wols				
				. (et al., 2014)				
Group II – High reactivity with ozone and RCS. Photo-resistant.											
							(Gerrity et al.,				
TMP							2012; Guo et				
	21	3×10^5	7 x 10 ⁹	² .46 x 10 ¹⁰	0.09	16	al., 2018; Wols				
							et al., 2014)				
Group III – Hi	gh reactivity with o	zone, and mod	~ate/low real	ctivity with RCS.	Photo-resista	nt.	. ,				
1	0 2			,			(Gerrity et al.,				
				2 x 10 ⁸	0.33	5.8	2012; Guo et				
CBZ	235	3 x 10	9 x 10 ⁹				al., 2018: Wols				
							et al., 2014)				
Group IV – Me	oderate reactivity v	ith cone. and	moderate/low	reactivity with	RCS. Moderate	e photosensitiv	vity.				
Group IV III		in e jone, and	moder and, to w	reactivity with	ites: mouerun	, photosensiti	(I am et al				
FLI	36	ΝΑ	9×10^9	N A	41	0.79	2005: Wols et				
TLU	50	N.A.	9 x 10	N.A.	41	0.79	2005, wors et				
							(Comity of al				
							(Genny et al.,				
GMF	116	5 x 10 ⁴	1 x 10 ¹⁰	4.16 x 10 ⁸	9.2	0.37	2012; Guo et				
							al., 2018; Wols				
_		_					et al., 2014)				
Group V – Low	v reactivity with ozo	one, and moder	rate/low react	ivity with RCS. I	Photo-resistant						
PRM	384	1	7 x 10 ⁹	6 x 10 ⁷	8.20	0.220	(Gerrity et al.,				

2012; Guo et

al., 2018; H. W.

Yu et al., 2015)

N.A.: not available

Southand

Parameter	Value
DOC (mg/L)	5.4
TN (mg/L)	2.4
UV ₂₅₄	0.148
pH	7.5

Table 2. Water quality parameters of tested wastewater.

Table 3. Fluorescing components determined in the tested wastewater by PARAFAC modeling and wavelengths corresponding to the positions of their excitation and emission maxima.

0	Wavelengths	of the maxi-	Description	Intensity before	Previously		
Component	ma (n	ım)	Description	treatment (RU)	reported by		
	Excitation	Emission					
					(Murphy et al.,		
Cl					2011; Sgroi et		
			W7 / / / / / / /		al., 2018a,		
	<250 & 350	440	Wastewater/nutrient enrichment	1.758	2017b; H. Yu		
			tracer, humic-like fluorescer		et al., 2015;		
					Yu et al.,		
					2010)		
					(Murphy et al.,		
					2011; Sgroi et		
<i>C</i> 2	<250 & 315	400	Micr. 'ial' umic-like fluorescence	1.047	al., 2018a,		
					2017b; H. Yu		
					et al., 2015)		
					(Murphy et al.,		
					2011; Sgroi et		
С3	<250 & 385	175	Fulvic-like and humic-like fluores-	0.870	al., 2018a,		
			cence		2017b; H. Yu		
					et al., 2015)		
					(Murphy et al.,		
					2011; Sgroi et		
<i>C4</i>	280	350	Protein, tryptopnan-like fluores-	0.672	al., 2018a,		
			cence		2017b; H. Yu		
					et al., 2015)		

Table 4. Observed first-order degradation rates (k_{obs}) for the investigated spectroscopic surrogates during different AOPs with indication of the coefficient of determination (R^2) , and their box-plot representation. k_{obs} are in [cm²/mJ] for UV/H₂O₂, UV/Cl₂ processes, and in [L/mg] for O₃, O₃/UV, H₂O₂/O₃/UV, Cl₂/O₃/UV processes.

0.002- K ^{ops} [cm ² /m ²] V 0.000	0.002- 0.001- 0.000- 0.000-				[L/mg]	0.6- 0.4- 0.2- 0.0 C	2 03M	³ O ³ ¹⁰⁴ O ³ ¹⁰⁴ C ¹⁴ O ³ ¹⁰⁴				
Treatment	С	1	<i>C</i> 2		$\overline{C3}$		<i>C4</i>		UV ₂₅₄			
1 reument	k_{obs}	R^2	k_{obs}	p ²	k_{obs}	R^2	k_{obs}	R^2	k_{obs}	R^2		
UV/H_2O_2	0.0008	0.987	0.0005	0.991	0.0003	0.975	0.0011	0.994	0.0002	0.752		
UV/Cl ₂	0.0014	0.984	0.001)	0.884	0.0007	0.872	0.0022	0.928	0.0007	0.904		
O_3	0.4183	0.966	0`859	0.983	0.1979	0.976	0.3597	0.995	0.1225	0.987		
O_{3}/UV	0.4093	0.957	0.2522	0.974	0.1993	0.998	0.3041	0.997	0.1463	0.991		
$H_2O_2/O_3/UV$	0.5065	0 712	0.2824	0.925	0.2403	0.948	0.5474	0.959	0.1742	0.870		
<i>Cl</i> ₂ / <i>O</i> ₃ / <i>UV</i>	0.6344	L 822	0.3809	0.838	0.3012	0.912	0.4644	0.952	0.2133	0.884		

Table 5. Observed first-order degradation rates (k_{obs}) for the target pharmaceuticals during different AOPs with indication of the coefficient of determination (R^2), and their box-plot representation. k_{obs} are in [cm²/mJ] for UV/H₂O₂, UV/Cl₂ processes, and in [L/mg] for O₃, O₃/UV, H₂O₂/O₃/UV, Cl₂/O₃/UV processes.



very fast = 100% removal was observed at the lowest oxidant dose; fast = 100% removal was observed at the second lowest oxidant dose.

Table 6. Summary of regression parameters for correlations between surrogates removal and pharmaceuticals removal with indication of most suitable index for the online monitoring (highlighted in italics and by colors).

		ΔR*	TN	ЛР	PI	RM	SN	ΛZ	C	BZ	F	LU GMF		MF
AOP	Index	(%)	slope	y-int	slope	y-int	slope	y-int	slope	y-int	slope	y-int	slope	y-int
	C1	39	1.561	16.93	1.188	4.97	1.155	34.29	1.303	17.26	1.464	21.05	1.180	13.92
H ₂ O ₂ /	C2	31	1.908	35.13	1.479	18.33	1.404	47.94	1.610	32.14	1.793	38.06	1.451	27.53
	C3	20	2.855	42.71	2.248	23.83	2.087	53.65	2.432	38.29	2.686	45.14	2.182	33.18
U V	<i>C4</i>	47	1.278	15.91	0.972	4.22	0.946	33.52	1.066	16.43	1.198	20.10	0.966	13.16
	UV ₂₅₄	6	9.109	-50.75	6.699	-43.38	6.829	-16.97	7.451	27.1.	8.513	-42.03	6.817	-36.30
	C1	32	-	-	1.156	-30.60	0.816	49.83	0.855	1'.65	2.299	-39.89	-	-
	C2	14	-	-	2.677	-76.44	1.908	16.83	1.990	-45.91	5.317	- 130.72	-	-
Cl ₂ /	C3	10	-	-	3.750	-79.79	2.681	14 .8	792	-48.54	7.440	- 137.23	-	-
0,	C4	21	-	-	1.685	-83.33	1.21	11.09	1.260	-51.49	3.339	- 143.93	-	-
	UV ₂₅₄	10	-	-	3.429	~7.84	2.472	22.20	2.564	-39.94	6.792	- 113.20	-	-
	C1	55	-	-	4ر 1.8	100.17	1.404	-21.43	-	-	3.058	- 172.09	2.506	- 119.87
O ₃	C2	56	-	-	¹ 704	-66.71	1.190	10.45	-	-	2.793	- 115.68	2.259	-70.46
	C3	49	-	$\overline{\mathbf{\cdot}}$	1.713	-49.37	1.126	26.39	-	-	2.756	-84.49	2.340	-49.42
	<i>C4</i>	64	-	-	1.320	-50.67	0.903	23.04	-	-	2.150	-88.41	1.764	-49.62
	UV ₂₅₄	37	-	-	2.198	-37.01	1.406	35.95	-	-	3.598	-66.87	2.753	-25.05
	C1	43	-	-	1.797	-90.74	0.710	36.97	-	-	1.185	-8.05	2.172	-95.63
01	C2	52	-	-	1.531	-46.23	0.582	55.89	-	-	1.019	20.77	1.782	-37.79
/UV	C3	55	-	-	1.401	-22.61	0.508	66.07	-	-	0.942	36.01	1.554	-6.68
	<i>C4</i>	61	-	-	1.249	-32.49	0.464	61.81	-	-	0.835	29.64	1.419	-19.71
	UV ₂₅₄	40	-	-	1.301	-13.33	0.591	64.21	-	-	0.827	44.33	1.805	-12.22
H ₂ O ₂ /	C1	19	-	-	1.950	-83.82	0.714	37.70	-	-	1.144	-2.15	1.617	-48.88
O ₃	C2	28	-	-	1.311	-9.26	0.456	66.42	-	-	0.740	43.33	1.053	14.96
/UV	СЗ	33	-	-	1.104	8.62	0.381	72.78	-	-	0.620	53.60	0.883	29.53
	C4	29	-	-	1.278	-35.10	0.464	55.89	-	-	0.745	26.87	1.054	-7.97

	UV ₂₅₄	20	-	-	1.725	-6.91	0.572	68.46	-	-	0.940	46.15	1.346	18.59
	C1	6	-	-	5.311	- 419.47	-	-	-	-	3.626	- 225.44	-	-
Cl ₂ / O ₃	C2	12	-	-	2.696	- 153.58	-	-	-	-	1.836	-43.58	-	-
/UV	C3	19	-	-	1.638	-65.43	-	-	-	-	1.117	16.31	-	-
	<i>C4</i>	23	-	-	1.330	-66.38	-	-	-	-	0.909	15.54	-	-
	UV ₂₅₄	15	-	-	2.147	-70.28	-	-	-	-	1.464	13.06	-	-

 $*\Delta R$ = width of the observed removal range for the surrogate parameters.

CRediT author statement

Massimiliano Sgroi: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing - Original Draft, Writing - Review & Editing, Visualization. Tarun Anumol: Formal analysis, Data curation. Federico G.A. Vagliasindi: Resources, Funding acquisition. Shane A. Snyder: Resources, Funding acquisition, Supervision. Paolo Roccaro: Conceptualization, Methodology, Formal analysis, Investigation, Data curation, Writing - Review & Editing, Visualization, Supervision, Funding acquisition.

Declaration of competing interests

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Highlights

- Comparison of UV/H₂O₂, UV/Cl₂, O₃, O₃/UV, H₂O₂/O₃/UV, Cl₂/O₃/UV at pilot scale
- Cl₂-based AOPs better degraded fluorescence organic matter than H₂O₂-based AOPs
- Cl₂-based AOPs showed higher selectivity to remove CEC than O₃ and H₂O₂-based AOPs
- Cl₂/O₃/UV was the most effective AOP to degrade target CEC except primidone
- The most sensitive surrogate for on-line monitoring was different for diverse AOPs

Solution















Cl₂/O₃/UV

















 $H_2O_2/O_3/UV$





Surrogate removal (%)

Figure 4