

UNIVERSITÀ POLITECNICA DELLE MARCHE Repository ISTITUZIONALE

Combined sewer overflows: A critical review on best practice and innovative solutions to mitigate impacts on environment and human health

This is a pre print version of the following article:

Original

Combined sewer overflows: A critical review on best practice and innovative solutions to mitigate impacts on environment and human health / Botturi, Alice; Ozbayram, E. Gozde; Tondera, Katharina; Gilbert, Nathalie I.; Rouault, Pascale; Caradot, Nicolas; Gutierrez, Oriol; Daneshgar, Saba; Frison, Nicola; Akyol, Çağrı; Foglia, Alessia; Eusebi, Anna Laura; Fatone, Francesco. - In: CRITICAL REVIEWS IN ENVIRONMENTAL SCIENCE AND TECHNOLOGY. - ISSN 1064-3389. - STAMPA. - 51:15(2021), pp. 1585-1618. [10.1080/10643389.2020.1757957] Availability:

This version is available at: 11566/277460 since: 2025-01-21T11:34:14Z

Publisher:

Published DOI:10.1080/10643389.2020.1757957

Terms of use:

The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. The use of copyrighted works requires the consent of the rights' holder (author or publisher). Works made available under a Creative Commons license or a Publisher's custom-made license can be used according to the terms and conditions contained therein. See editor's website for further information and terms and conditions. This item was downloaded from IRIS Università Politecnica delle Marche (https://iris.univpm.it). When citing, please refer to the published version.

Publisher copyright:

Taylor and Francis - Preprint/Author's submitted Manuscript

This is an original manuscript of an article published by Taylor and Francis in CRITICAL REVIEWS IN ENVIRONMENTAL SCIENCE AND TECHNOLOGY on 2021, available at: https://doi.org/10.1080/10643389.2020.1757957

1	Combined Sewer Overflows: A critical review on best practice and innovative solutions to
2	mitigate impacts on environment and human health
3	Alice Botturi ¹ , E. Gozde Ozbayram ^{2*} , Katharina Tondera ³ , Nathalie I. Gilbert ⁴ , Pascale
4	Rouault ⁵ , Nicolas Caradot ⁵ , Oriol Gutierrez ⁶ , Saba Daneshgar ¹ , Nicola Frison ¹ , Çağrı
5	Akyol ⁷ , Alessia Foglia ⁷ , Anna Laura Eusebi ^{7*} , Francesco Fatone ⁷
6	¹ Department of Biotechnology, University of Verona, 37134, Verona, Italy
7	² Faculty of Aquatic Sciences, Istanbul University, 34134, Istanbul, Turkey
8	³ IMT Atlantique, GEPEA, UBL, F-44307 Nantes, France
9	⁴ Thames21, London, UK
10	⁵ Kompetenzzentrum Wasser Berlin (KWB), Berlin, Germany
11	⁶ Catalan Institute for Water Research, ICRA Scientific and Technological Park of the University
12	of Girona, Emili Grahit 101, 17003 Girona, Spain
13	⁷ Department of Science and Engineering of Materials, Environment and Urban Planning-
14	SIMAU, Faculty of Engineering, Polytechnic University of Marche, 60121, Ancona, Italy
15	* Corresponding author (A.L. EUSEBI)
16	Department of Science and Engineering of Materials, Environment and Urban Planning-SIMAU,
17	Faculty of Engineering, Polytechnic University of Marche, 60121, Ancona, Italy
18	E-mail: <u>a.l.eusebi@univpm.it</u> , Phone: +39 071 2204911 Fax: +39 071 2204729
19	*Corresponding author (E.G. OZBAYRAM)
20	Faculty of Aquatic Sciences, Istanbul University, 34134, Istanbul, Turkey

E-mail: gozde.ozbayram@istanbul.edu.tr, Phone: +90554 734 6496

22 Abstract

23	Combined sewer overflows (CSOs) are of major environmental concern for impacted surface
24	waterbodies. In the last decades, major storm events have become increasingly regular in some
25	areas, and meteorological scenarios predict a further rise in their frequency. Consequently,
26	control and treatment of CSOs with respect to best practice examples, innovative treatment
27	solutions and management of sewer systems is an inevitable necessity. As a result, the number of
28	publications concerning quality, quantity and type of treatments has recently increased. This
29	review therefore aims to provide a critical overview on the effects, control and treatment of CSOs
30	in terms of impact on the environment and public health, strict measures addressed by
31	regulations, and the various treatment alternatives including natural and compact treatments.
32	Drawing together the previous studies, an innovative treatment and control guideline is also
33	proposed for the better management practices.
34	
35	
36	Keywords: Combined sewer overflows; nature based solutions; sewer system; urban water
37	management; water quality

38

39 Abbreviations

BFU	Ballasted Flocculation Unit
BOD ₅	Biochemical Oxygen Demand
BWD	Bathing Water Directive
COD	Chemical Oxygen Demand
CSO	Combined Sewer Overflow
CSS	Combined Sewer System
CW	Constructed Wetland
EPA	United States Environmental Protection Agency
GAC	Granular Activated Carbon
NBS	Nature based solutions
NPDES	National Pollutant Discharge Elimination System
OCC	Optimum Coagulant Concentrations
РАА	Peracetic Acid
PFA	Performic Acid
RSF	Retention Soil Filter
SSO	Sanitary Sewer Overflow
SUDS	Sustainable Urban Drainage System
TKN	Total Kjeldahl Nitrogen
TSS	Total Suspended Solid
UVT	UV Transmittance
UWWTD	Urban Waste Water Treatment Directive
WFD	Water Framework Directive

WWTP	Wastewater Treatment Plant

41 **1. Introduction**

The European Water Framework Directive (WFD, 2000) is the key policy driver in the water 42 sector focusing on management strategies for improving water quality and protection of the 43 receiving bodies from wastewater effluent discharges. It emphasizes the control of diffuse 44 45 pollution as a major factor in enabling good ecological status in all waterbodies of member states. Wastewater and storm water collection, as well as their management, are crucial services 46 protecting public health and the environment, thus appropriate receiving systems facilitate urban 47 development. Additionally, countries also develop national regulations to sustain environmental 48 protection and to better manage the sewage systems. 49 In Europe, there are two major system types to collect and transport wastewater: the separate 50 system and combined system and modified versions thereof. In the separate system, the waste 51 water and storm water are transported in two separate pipelines (Figure 1a). The sewage from 52 households and industry is carried to wastewater treatment plants (WWTPs) and the storm water 53 is discharged into the nearest waterbody, usually only with physical pre-treatment. Although 54 runoff from urban surfaces may collect contaminants along the way (such as pathogens, 55 hydrocarbons, grit, sediment, chemicals and heavy metals), this discharge does not generally 56 require an environmental permit and it is usually consented by environmental regulators (Jotte, 57 58 Raspati, & Azrague, 2017).

In the combined sewer system (CSS), sewage and storm water are carried in one unified sewer
network to the centralized WWTP. Under dry weather conditions, the CSS only collects
municipal and industrial wastewater, but this is mixed with surface runoff under wet weather
conditions.

In modified sewer systems, rainwater is treated according to its pollution: infiltration of

minimally contaminated roof runoff, transport of storm water from low trafficked roads, streets 64 and pavements by open drains or the direct use for landscaping purposes is possible. 65 However, all sewer infrastructure is limited in its capacity for water intake and transport. Usually, 66 CSSs are unable to cope with the flows experienced during heavy rain events, so a relief 67 68 mechanism is inserted in the wastewater network which is a combined sewer overflow infrastructure. This directs excess flows, comprising a mixture of untreated raw sewage and storm 69 water, to the receiving waterbodies. These structures are used to maintain the flowrates in the 70 71 network and protect properties from potential flooding (Bailey, Harris, Keedwell, Djordjevic, & Kapelan, 2016). 72 Up to date, limited information has been published internationally concerning the extent and 73 occurrence of CSOs and discharge points. It is estimated that there are 2.2 million km of existing 74 sewerage systems in Europe, of which approx. 70% of the total network is combined sewers. 75 Moreover, there are approx. 650.000 CSOs and their impact on the receiving waterbody is an 76 increasing concern across Europe (EurEau, 2016). Some information can be obtained from 77 reports submitted to the European Union by member states. E.g. in 2012, Germany submitted a 78 request to extend the deadline of fulfilling the goals of the Water Framework Directive (reaching 79 a "good" ecological and chemical status of 80% of surface waterbodies by 2015) until 2027. In a 80 81 summary of the 2012 report to the European Commission (BMU, 2013), the authors describe that 10% of the key measures required reach the good status pertain to sewer systems and municipal 82 83 wastewater treatment plants. From the total number of these key measures mentioned in the 84 report, approximately 28% of them concern storm water in combined and separate sewer systems 85 and only 12% of them has a connection to the sewer system in general (UBA, 2012). Since this

report does not mention costs or the kind of measures taken to reach the EU targets, it still

remains unclear which role measures in the CSS play in relation to others.

88	The American Society of Civil Engineers estimated that the infrastructure for CSO control may
89	cost around \$45 billion, which is the largest necessity in the water/wastewater sector for the
90	country (Ruggaber & Talley, 2005). Today, in the USA there are 746 communities with CSSs
91	containing a total of 9,348 CSO outfalls that are identified and regulated by 828 National
92	Pollutant Discharge Elimination System (NPDES) permits. CSSs are found in 32 states and nine
93	EPA (Environmental Protection Agency) Regions. CSO communities are regionally
94	concentrated in older communities in the Northeast and Great Lakes regions. The EPA estimates
95	that approx. $3.9 \cdot 10^9 \text{ m}^3$ of untreated combined sewage is released as CSOs each year in the
96	United States (US-EPA, 2004).
97	Since CSOs result from a mixture of raw sewage and storm water, they possess a serious threat of
98	microbial pathogens (Al Aukidy & Verlicchi, 2017), micropollutants from personal care products
99	(Heinz et al., 2009), hormones Phillips et al., 2012), pharmaceutical and illicit drugs (Munro et
100	al., 2019), pesticides (Gasperi et al., 2012; Launay, Dittmer, & Steinmetz, 2016), suspended
101	solids, heavy metals, nutrients and microplastics in surface waterbodies (Al Aukidy & Verlicchi,
102	2017; Kistemann, Schmidt, & Flemming, 2016; Madoux-Humery et al., 2015; Masi, Rizzo,
103	Bresciani, & Conte, 2017; Munro et al., 2019; Suárez & Puertas, 2005; Tanaka & Takada, 2016;
104	Tondera, Koenen, & Pinnekamp, 2013; Xu et al., 2018). Meteorological and climate change
105	predictions indicate an expected rise in the frequency and intensity of storm events with the
106	implication that sewer system capacity will be exceeded more regularly. Furthermore, increased
107	base flow in sewers due to trends for increasing urbanization and population growth in many
108	cities worldwide means sewers fill up faster, which increases the likelihood of overflows during
109	smaller rain events. Expansion of urban areas also leads to an increase of impermeable surfaces

within catchments and faster surface water runoff, which also influences the frequency of CSOs(Schertzinger et al. 2018).

Publications on treatment and control alternatives for CSOs are limited in number. More studies 112 should focus on best practice and innovative solutions for treatment and management of sewer 113 systems and recently there has been an increase in literature concerning the quality, quantity and 114 type of treatments (Masi et al., 2017; Rizzo et al., 2018; Ruppelt, Tondera, Vorenhout, Van der 115 Weken, & Pinnekamp, 2019; Tondera, 2017). Since sustainable city approach requires reducing 116 117 impacts of wastewaters in aquatic environments, integrated strategies should be evaluated within this context. Additionally, smart network monitoring and smart data infrastructures (US EPA, 118 2018) are currently under development and application. These infrastructures are implemented in 119 connection with a supervisory control and data acquisition (SCADA) system and are mainly 120 focused on real-time monitoring of flow rates (physically or with alternative methods) and 121 effluent levels in CSO's with the aim of assessing potential flooding and pollution incidents and 122 to support real-time or quasi real-time decision making about actions to be taken. Research and 123 innovation play an important role in the implementation and improvement of new technologies 124 and approaches in this field. Changes of frequency and intensity of rain events increase the 125 pressure on meeting the requirements stated in the EU regulations (e.g. Water Framework 126 Directive, Bathing Water Directive) and national legislations; thus, to integrate the reduction 127 measures, several projects were founded within this scope. The EU 7th Framework Program for 128 Research and Innovation funded more than 140 research and innovation projects related to this 129 topic in the period 2007-2013, and other projects are being supported by Horizon 2020 130 Innovation funding. For example, one aim of the INTCATCH H2020 Project (http://intcatch.eu/), 131 132 is technological innovation and integration in smart water monitoring in the treatment of CSOs

before their discharge into a waterbody. A pilot plant was installed and operated for about two
years on Lake Garda, Italy, to demonstrate the concept of technological innovation and public
participation in the integrated and smart management of water infrastructures and basins.
Taken together, the attempt of this review is to develop better understanding on CSOs by
exploring the impact and mass load in terms of quantity and quality, treatments possibilities, both
as conventional and more innovative options, guidelines to management and actual policy and
future recommendations.

140 **2.** The characteristics of combined sewer overflows

Climatic factors such as quantity and intensity of precipitation are key factors determining the 141 severity of CSO discharges. The characteristics of combined sewage are dependent on rainfall 142 intensities and pollutant concentration and loads affected by wet and dry weather conditions 143 (Sandoval, Torres, Pawlowsky-Reusing, Riechel, & Caradot, 2013). Moreover, during 144 145 transportation in the sewer system, the physical, chemical and biological characteristics of wastewater changes (Nielsen, Raunkjær, Norsker, Jensen, & Hvitved-Jacobsen, 1992). 146 147 The relationship between rainfall, flood and overflow frequencies on water quality in CSO discharges are nonlinear (Willems, 2012). Climate change also has a major impact on CSO 148 149 volumes for the regions where heavy rainfall events occur more frequently. As such, CSO discharges represent a great challenge to meeting required water quality standards in locations 150 with CSSs. How CSOs impact the water quality of the receiving bodies should be evaluated in an 151 152 integrated manner considering the flows, concentration and season in which the impact is more destructive – in Europe this is usually during low flow regimes during summer months (Willems, 153 2012). As this is also a period of increased recreational activities in surface waterbodies 154 (Kistemann et al., 2016), severe health ramifications can be linked to CSO discharges (McBride, 155

156	Stott, Miller, Bambic, & Wuertz, 2013). Monitoring studies indicate that the frequency of CSOs
157	has increased in recent years. Whereas 9 CSO events were observed in 2012 in Lodz, the third
158	largest city in Poland, the number increased to 23 in 2014 which exceed the number permitted by
159	the legislation (10 times per year, Brzezińska et al., 2016) (Table 1). Similarly, CSO frequency
160	and volume also increased by varying amounts in England (Willems, 2012). It is clear from the
161	table that low number of events were analysed compared to the number of CSOs registered in the
162	study area. In another study, Al Aukidy and Verlicchi, (2017) reported 20 CSO events within 3
163	months in the Po Valley, Italy. The total overflow volume ranged between 18-16.299 m ³ , the
164	volume increased over years. Heinz et al. (2009) indicated that 9-10 overflow events occur in
165	Gallusquelle region in Germany annually with an average discharge of approximately 23,000 m ³ .
166	In the River Thames, London, approx. 39 million tons of untreated sewage enters the river
167	annually from approx. 57 different CSO locations (Munro et al. 2019). Madoux-Humery et al.
168	(2016) carried out their study in Québec (Canada) where the annual precipitation falling as
169	rainfall is 625 mm/year and average cumulative precipitation falling as snow of approximately
170	2000 mm/year. They observed 2258 CSO events during the 2009-2011 period. Soriano and Rubió
171	(2019) stated that there are 35 overflow points located along the Ebro river in which many of
172	these overflow points have two to four discharge points, overall there are 72 overflow points in
173	Ebro river.



Table 1. The combined sewer overflow monitoring

Area	Monitoring Strategy	N° of events in the study area	N° of events analyzed	Period of study	Rain amount (mm)	Overflow discharged volume (m ³)	Reference
Lodz, Poland	Sewer flowmeters located in the cathment	9 – 28/year	60	3 years		3.600- 49.822/year	Brzezińska, 2016
Po Valley, Italy	the CSO outfalls are located within the lifting pump stations	-	41	3 months (2014)	740/year	18-30383/event	Al Aukidy and Verlicchi, 2017
Gallusquelle, Germany	-	10/year	5	5 months (2005)	-	23.000 (5 events)	Heinz et al., 2009
Québec, Canada	Overflow markers, continuous data recorders and automatic data recorders	160/year (from 2009-2012)	-	-	-	-	Jalliffier-Verne et al., 2015
Stuttgart, Germany	Flowmeter	-	7	3 months (2014)	-	-	Launay et al., 2016
Québec, Canada	-	2258 (from 2009- 2011)	5	-	625/year	92-19.530 (5 events)	Madoux- Humery et al., 2016
Vermont, USA	-	37 (from December 2007- November 2008)	-	1 year (2007- 2008)	20-410/day	-	Phillips et al., 2012
Spain	-	-	46	-	-	2752-41.566/event	Suarez and Puertas 2005
Berlin, Germany	179 CSO discharge points 14 CSO	37/year (from 2000-2007)	-	-	-	7x10 ⁶ /year	Weyrauch et al., 2010
La Garriga, Spain	infrastructure with low-cost	36-49 (in 11 month)	-	1 year (2011- 2012)	0.4-51.4/episode	-	Montserrat et al., 2015
Paris, France	Dry weather: daily	-	-	-	20.1/rainfall event	3.2x10 ⁶ /year	Gasperi et al.,

	samples for the 4						2008
	upstream sites. Wet						
	weather: 4 of the 45						
	CSO sampled						
The Aire and Calder	Samples from						
catchements, West	WWTP, CSO and	-	5	-	-	-	Kay et al., 2017
Yorkshire, UK	receiving water						
City of Santiago de	_	_	925	4 years (1995-	1600/vear	_	Diaz-Fierros et
Compostela, Spain	-	-	125	1999)	1000/ year	-	al., 2002
Gorla Maggiore,	60 CSO events	60 CSO events	60	1 year (2014-		87.570/event	Masi et al 2017
Italy	0) CSO events	0) CSO events	07	2015)		87-379/event	Widsi et al., 2017
177							

Table 2. The characteristics of combined sewer overflows

Study site	Monitoring strategy	TSS (mg/L)	BOD ₅ (mg/L)	COD (mg/L)	TN (mg/L)	N-NH ₄ (mg/L)	TP (mg/L)	Reference
Slovakia	8 CSO stations	430	175	445	16.8	6.21	2.63	Sztruhár et al., 2002
Gorla Maggiore, Italy	68 CSO events	-	-	176- 612	-	3.8-28	-	Masi et al., 2017
Boudonville retention basin, Nancy, France	During rain events, CSO samples every 5-10 min	182.29- 869.6	-	-	-	-	-	Samrani et al., 2008
Paris, France	Dry weather: daily samples for the 4 upstream sites. Wet weather: 4 of the 45 CSO sampled	150-700	-	-	-	-	-	Gasperi et al., 2008
Paris, France	4 CSO stations	135-353	36-180	136- 446	-	3.3-9.3	1.2-5.4	Gasperi et al., 2012
General characteristics	-	270-550	60-220	260- 480	-	-	-	Metcalf and Eddy, 1991
Harlem River, Bronx side, New York. The USA	50 CSO stations	-	-	-	-	1.3-2.7	0.5-3	Wang, 2014
North-Rhine Westphalia, Germany	>20 retention soil filters for CSO treatment	1-1123	-	15-918	-	-	0.1- 16.1	Tondera, 2017
Shanghai, China (combined)	-	91-529	111- 178	243- 484	-	7.6- 17.2	-	Li et al., 2010
Germany	-	174.5	60	141	12.6	1.94	1.25	Brombach et al., 2005
Two cities in Korea	from June 1995 to November 1997	99.0-215.7	33.7- 81.5	118.5- 223.5		-	-	Lee & Bang, 2000
	-	1-4420	3.9- 696	-	-	-	0.1- 20.8	EPA, 2004
The United States	-	237-635	43-95	120- 560	2.9-4.8	-	-	Ellis and Jenkins, 2005
Canada	-	190	-	-	8.3	-	1.4	Ellis and Jenkins, 2005
United Kingdom	-	425	90	260- 507	8.3	-	10	Ellis and Jenkins, 2005
Europe	-	105-721	39.9- 200	148- 530	2.1- 14.4	-	2.4-4.0	Ellis and Jenkins, 2005

Santiago de Compostela, Spain	Monitoring over a 40-month period	160-411	70.5- 171	134- 540 -	5.2- 12.8	0.5-4.6	Diaz-Fierros et al., 2002
Louisville, Atlanta	-	14-227	-	40-107 -	-	-	Arnone and Walling, 2006

3. Water quality impacts of CSO discharges

The pollutants released with CSO discharges can have detrimental impacts on aquatic 181 environments and public health. The pollutants in the untreated wastewater can increase the 182 organic content of receiving water bodies and oxygen depletion occurs with biodegradation, 183 184 promoting eutrophication. In a comprehensive study carried out by Viviano et al. (2017), it was reported that more than 50% of the total phosphorous loads in the Lambro River resulted from 185 CSO discharges during heavy rain events. Thermal pollution may also occur where the 186 187 temperature of the CSO is different to the receiving water. Moreover, as a consequence of increased turbidity, photosynthesis is inhibited/reduced (Riechel et al., 2016). In warm seasons, 188 low flows can limit dilution effects and, therefore, increase the problem (Montserrat, Gutierrez, 189 Poch, & Corominas, 2013). On the other hand, the concentrations of wastewater contaminants 190 such as total solids, COD, TKN, and Ptot can decrease due to the dilution caused by high 191 precipitation. The study carried out by Gasperi, et al. (2012) showed that the parameters can be 192 decreased almost one-third of the dry season (Table 2). On the other hand, a high variation 193 between maximum and minimum values for the parameters were determined in various studies 194 195 (El Samrani, Lartiges, & Villiéras, 2008; Li, Tan, & Zhu, 2010; Tondera, 2017; U.S.EPA, 2004) and the highest values were reported by EPA (2004) in which TSS, BOD₅, and TP were 196 determined as 4420 mg/L, 696 mg/L, and 20.8 mg/L. The variation could be attributed to the 197 precipitation volume, duration, location, etc. and confirmed the high stochastic nature of CSO 198 events Masi et al. (2017). 199

Emerging contaminants, such as pharmaceuticals, hormones and substances from personal care products, can be introduced into aquatic environments via CSO discharges (Del Río et al., 2013; Montserrat et al., 2013; Passerat et al., 2011)). These contaminants may also be mobilized from

sediments during storm events and end up in the water (Del Río et al., 2013). The runoff from 203 urban surfaces transports additional loads of heavy metals, polycyclic aromatic hydrocarbons and 204 a variety of other micropollutants such as pesticides Gasperi et al., 2014; Phillips & Chalmers, 205 206 2009). Metals contamination is another important issue in CSO discharges, which can accumulate in the sediment and affect the aquatic ecosystem, for example by inhibiting reproduction in 207 sensitive macroinvertebrates (Schertzinger, Ruchter, & Sures, 2018). A correlation between 208 209 metals concentration in the sediment and the number of CSOs were determined by Hnaťuková (2011). 210

Recent studies revealed that, even though CSO discharges represent only a small proportion of 211 the total annual wastewater discharge, these overflows contribute to 30-95% of the annual load 212 for different pollutants including caffeine, ibuprofen, polycyclic aromatic hydrocarbons (PAHs), 213 phenolic xenoestrogens, hormones, and urban pesticides (Launay et al., 2016; J. P. Phillips et al., 214 2012). Furthermore, Phillips et al. (2012) stated that micropollutant concentrations could be up to 215 10 times higher in CSO discharges than that of the treated wastewater. Despite the short duration 216 of CSO discharges, they introduce, high loads of micropollutants into waterbodies (Musolff et 217 218 al., 2009). Moreover, the concentrations of PAHs in CSO discharges were found 2000 times greater than Environmental Quality Standards (Birch, Mikkelsen, Jensen, & Holten Lützhøft, 219 2011). Gasperi, et al. (2012) evaluated the concentrations of priority pollutants as well as 220 221 wastewater quality parameters for CSO discharges, wastewater, and storm runoff. Whereas runoff is the major source for pesticides and dissolved metals (e.g. Zn) in CSO discharges, 222 wastewater is the main contributor to volatile organic compounds. On the other hand, 223 hydrophobic organic pollutants (e.g. PAHs, APnEOs) and particulate-bound metals (e.g. Pb and 224 225 Cu) are mostly caused by in-sewer deposit erosion in the CSO discharges. Although wastewater

226	effluents and CSO discharges are the main contributors for endocrine-disrupting compounds and
227	personal care products in receiving water bodies, the concentrations depend on the removal rates
228	in wastewater treatment plants, stormwater dilution factor, and the quantity of wastewater
229	bypassed the treatment plant (Ryu, Oh, Snyder, & Yoon, 2014). Studies suggest some substances
230	suitable as markers for CSOs, especially those which are biologically degraded in WWTPs or are
231	specific to stormwater runoff. In combined sewer networks, caffeine can be proposed as a tracer
232	for CSO discharges (Buerge et al., (2006). Similarly, Fono and Sedlak (2005) introduced
233	propranolol, a pharmaceutical component, as a tracer for anthropogenic discharges.
234	CSO discharges introduce infectious pathogens originating from human faces and organic waste
235	in the sewage, as well as from animal feces in run-off originating from wildlife (e.g. birds) or
236	domestic animals (especially dogs) (Schares et al., 2005). They can contain antibiotic resistant
237	bacteria (Young, Juhl, & O'Mullan, 2013).
238	Monitoring programs usually focus on indicator organisms, such as E. coli and intestinal
239	enterococci, which are e.g. relevant for the EU Bathing Water Directive, or thermo-tolerant
240	coliforms (WHO, 2008). They are chosen to indicate specific pollution, e.g. by fecal
241	contamination. Ideally, this should enable one to conclude that a health risk is present. Some
242	studies have investigated and detected further bacterial pathogens such as Campylobacter,
243	Salmonella, Aeromonas spp., P. aeruginosa; enteric viruses such as Adenovirus and Norovirus,
244	and human polyomavirus as well as protozoan parasites such as Giardia lamblia and
245	Cryptosporidium (Christoffels, Mertens, Kistemann, & Schreiber, 2014; McGinnis et al., 2018;
246	Tondera et al., 2015).
247	Direct measurements in CSO discharges regarding E. coli concentrations are rare; more often,

248 polluted river water after overflow events is sampled instead. In the few published investigations

with direct measurements, the median concentrations of *E. coli* at the outlet of overflow or CSO
retention tanks range from 10⁴ to 10⁶ MPN or CFU/100 mL (Stott, Tondera, Blecken, &
Schreiber, 2018).

252 If surface waters are used for recreational purposes, these microbial contamination result in risks of infections with gastrointestinal illnesses, pneumonia, bronchitis, and respiratory infections 253 (U.S.EPA, 2004). McBride et al. (2013) revealed that the highest risks for swimmers derive from 254 255 noro- and rotaviruses in such contaminated waters. Pond (2005) gives a detailed overview on infections and sequelae caused by these pathogens, some of which are chronic. The author 256 associates the discharge of CSOs with these diseases and recommends closing recreational areas 257 after heavy storm events and sewage treatment in general as a management strategy against 258 possible infections. Accordingly, Tondera et al. (2016b) modelled the overall impact of CSO 259 discharges on microbial contaminations in the Ruhr River relative to other sources, e.g. from 260 WWTP effluent or diffuse pollution. The authors showed that in the river, which passes through a 261 densely populated area in Germany, CSO discharges had the highest impact on elevated 262 263 microbial concentrations up to two days after rainfall events. Moreover, Jalliffier-Verne et al. (2016) stated that high E.coli concentrations at raw water collection points for drinking water 264 production correlate with the discharged concentrations from CSOs, the location of overflows, 265 266 dispersion processes in the surface waterbody, and the season. In a study carried out by Riechel et al. (2019), the authors used a tracer approach using wastewater volume as a proxy for pathogen 267 emissions to assess the relationship between different CSO outlets and bathing water quality for 268 Berlin, Germany. According to their results, wastewater including only 5% of the CSO volume 269 contributes >99% of the pathogen loadings to the receiving environment. Wastewater volume 270 was also of relevance for determination of point sources for the hygienic impairment of the 271 receiving environment. In another study by the same group (Seis, Zamzow, Caradot, & Rouault, 272

2018), they proposed a methodology which demonstrated the shortcomings of current long-term
classification as well as the potential for improvement by applying the proposed approach
regarding to the microbial safety. However, USEPA's BEACH Program conducted an annual
survey of the nation's swimming beaches. During the 2002 swimming season, CSOs and SSOs
were responsible for only 1 and 6 percent, respectively, of reported advisories and closings
(USEPA, 2004). Therefore, results are controversial and call for proper smart monitoring and
case-by-case analyses.

4. Policy, legislation, governance and regulation to address the challenges

The necessity of controlling CSO pollution under the urban wastewater treatment directive (UWWTD; OJEC 1991) and water framework directive (WFD; OJEC 2000) was stated by the European Union. Discharges of CSOs may affect the achievement of "good status" of waterbodies as required by the European Water Framework Directive. The scientific community and the water sector operators are raising awareness of the environmental problems relating to CSOs and are promoting initiatives for reduce their impact and improving the quality of surface water (EurEau, 2016).

288 Since 1998, there have been significant changes in legislation with the implementation of the 289 water directives; and water quality and ecological standards have been revised. New issues have 290 arisen with an urgent need of adaptation and mitigation measures in the upgrading of urban drainage systems. In the European legislation relating to CSOs, it is possible to distinguish 291 292 between Directives aimed at protecting receiving waters and Directives to control CSO 293 discharges (Morgan, Xiao, & McNabola, 2017). The Urban Waste Water Treatment Directive 91/271/EEC (UWWTD) highlights that the collecting systems shall be constructed and managed 294 295 in accordance with limiting the quantity of pollution entering receiving waters due to storm water

296	overflows. In addition, the UWWTD requires reporting of wastewater sewerage treatment
297	performance and a system of pre-authorization for all wastewater discharges, including CSOs.
298	The ongoing evaluation of the UWWTD has highlighted the importance of better managing
299	CSOs. The Bathing Water Directive 2006/7/EC (BWD) and the Habitats Directive 92/43/EEC are
300	limited to assess the bathing waters affected by CSOs as "subject to short-term pollution". In the
301	EU Regulation No. 166/2006 (2006)" concerning the establishment of a European Pollutant
302	Release and Transfer Register", EU member states are obligated to report pollutant loads,
303	specified in Annex II, to water. The threshold values are also specified in this regulation. Thus,
304	the pollutant loads from CSO discharges should also be estimated. However, this is very
305	challenging since CSO structures are not designed for monitoring purposes.
306	CSO discharges have been identified as an important problem for European countries. Germany,
307	UK and other countries have started to establish CSO policies and actions before Water
308	Framework Directive (Malgat, 2013). Sixteen EU member states have national standards that
309	regulate storm water overflows, eleven of them have guidance documents that directly address
310	storm water overflows (EurEau, 2016). Common approaches in standards and guidance are:
311	- Limit on the number of overflows (e.g. Belgium, Poland, Portugal);
312	- Requirements for dilution (e.g. Bulgaria, Czech Republic, Estonia);
313	- Other approaches seen: max total volume, or max number of days of overflows (e.g.
314	Germany).
315	The permitted number of overflows per year proposed by CSO regulation guidelines differs
316	according to each member country and ranges from 2-3 in Denmark and the Netherlands, 15-20
317	in the Galician region in Spain (Table 3, Montserrat et al., 2015) and 10 in Poland (Brzezińska et
318	al., 2016).

Table 3. Regulations issued CSOs

Country	Regulation/Legislation/Guideline	Issue
Italy	Regulation Number 917/2017	Number of overflows per year
Denmark	Danish Nature Agency, 2011:55	Number of overflows per year (2-3)
Netherlands		Number of overflows per year (2-3)
Spain	Royal Order RD 1290/2012	Number of overflows per year (15-20)
UK	The Urban Wastewater Treatment	Number of overflows per year (15-20)
	Regulations 1994, Regulation 6 (2)	
Canada	MDDELCC, 2014	New developments will not result increase in
		the frequency of overflows
Japan	Enforcement Ordinance of Sewerage	BOD ₅ parameter
	Law (2003)	
Australia	Environment Protection Authority, a	Implementation of overflow abatement
	Code of practice	program
France	Local Authorities General Code	Monitoring must be ensured by the operator,
	2015 Order	municipality and the different water policy
		services

320 In the UK the requirements for solids separation depend on the number of overflows per year.

The Urban Wastewater Treatment Regulation (6 (2), 1994), states that primary treatment must be

provided within CSO structures, in which the biological oxygen demand, determined over 5 days,

323 (BOD₅) of the incoming wastewater is reduced by at least 20% before discharge and the total

324 suspended solids reduced by at least 50% (Morris, 1999). The third periodic Asset Management

325 Plan review (AMP3: 2000–2005) specified a timetable for water companies to reduce the number

of unsatisfactory intermittent discharges caused by CSOs (McSweeney et al., 2009). In 2012, a

327 comprehensive framework for CSO improvement has been developed through the urban pollution

management program to assess the impact of CSO discharges on receiving water quality and to

develop water quality standards for the protection of aquatic life from intermittent pollution

caused by CSO discharges (Morgan et al., 2017). These criteria also form the basis of CSO

assessment in Ireland, as set out in the Procedures and Criteria in relation to Storm Water

332 Overflows. On the other hand, in Italy, a list of performance indicators to describe the technical

quality of the water utility management and operation were introduced in 2017 by the Italian

Regulatory Authority for Energy, Networks and Environment (Regulation Number 917/2017). 334 The section dedicated to the sewer system includes two restrictions; firstly, the adequacy of the 335 CSO stations and secondly, the number of overflows allowed in one year in each 100 km of 336 337 sewage system. Moreover, in Spain, the Royal Order RD 1290/2012 requires that all CSO discharging points for places exceeding 2000 equivalent inhabitants be defined (Montserrat et al., 338 2013). In France, it is just stated that CSOs spillages must not exceed 2% of the total average 339 340 annual volume for 5 years (Tabuchi, 2013) and according to the "Local Authorities General Code 2015 Order" monitoring must be ensured by the operator, municipality and the different water 341 policy services. However, in Germany, several guideline describe the design and construction of 342 CSO retention tanks at points with critical discharge (ATV-128, 1992; DWA, 2013b, 2013a). 343 Capacities depend on factors like the catchment area, population density, historical rainfall 344 patterns and the proportion of impervious surface areas. The percentage of wastewater in a 345 catchment that can be discharged via overflows is based on ten-year rainfall patterns and 346 determined by the sensitivity of the receiving waterbody. In 1994, the United States 347 348 Environmental Protection Agency issued the combined sewer overflow control policy in the National Pollutant Discharge Elimination System program (NPDES). Within the scope of the 349 policy, site-specific permits were developed for all CSS considering cost/performance in relation 350 351 to the size of the individual systems. Additionally, a list of nine minimum measures were determined for CSOs in order to develop and adopt long term control plans (U.S. EPA, 2001; 352 U.S.EPA, 2004). They include programs for control measures during installation and pollution 353 prevention, pre-treatment applications, maximization of the storage in collection system and flow 354 directed to the WWTP, monitoring, as well as public communication. In Canada, although there is 355 no federal legislation for CSOs control, some provinces, like Quebec, adopted specific rules to 356 restrict CSOs (MDDELCC, 2014). To be in accordance with the Strategy for the Management of 357

Municipal Wastewater Effluent, municipalities and developers have to demonstrate that new 358 developments will not result in an increase in the frequency of CSO (Mailhot, Talbot, & 359 Lavallée, 2015). According to the Canada-wide Strategy for the Management of Municipal 360 Wastewater Effluent, CSO discharges are not entirely prohibited, but are allowed in exceptional 361 circumstances, such as during snow-melt in spring time (Jalliffier-Verne et al., 2016). Differently, 362 in Japan, in 2003, an amendment of "Enforcement Ordinance of Sewerage Law" related to CSO 363 364 discharges abatement was issued defining the BOD₅ concentration in the effluent overflow (< 40 mg/L), allowing a provisional limit of 70 mg/L applicable until structure standards start to be 365 applied. Small and midsize municipalities were obligated to implement improvements by 2013, 366 large municipalities by 2023. Environment Protection Authority of South Australia issued a code 367 of practice for wastewater overflow management giving a roadmap to the operators to comply 368 with their environmental obligations. The water utility is obligated to implement an overflow 369 abatement program, which encompasses an emergency response plan and short- and long-term 370 measures to prevent or reduce the re-occurrence of overflows. However, in South Africa the 371 372 policy related to runoff water disposal asserts that: "Urban stormwater discharged to the marine environment should not have any negative impact on the Environmental Quality Objectives of the 373 receiving environment", it does not provide specification on treatment-at-source or land-based 374 375 treatment, which are considered specific to disposal of stormwater runoff.

Overall, different directives have been developed worldwide, which are mainly focused on the affirmation of the negative effects of the CSO events and allowed a number of overflows per year. Generally, the policymakers are revising and deriving the regulations to enforce authorities to take pre-cautions and control CSO discharges. Although they pointed out the adverse impacts, in many countries no specific limits for water parameters have not been set to limit pollution from CSO

discharges. This aspect is mainly related to the great variability in terms of quality and quantity of

382 CSO characterization in the different sewer systems, previously described in the Section 3.

383 Moreover, wide sampling campaigns and monitoring methods have to be implemented in order to

quantify the hydraulic and the characterization conditions to support the legislation improvements.

Finally, specific treatment technologies and control measures can be integrated into the regulations.

386 **5. Innovative methods for CSO determination**

- ³⁸⁷ Hydraulic conditions are the main factor to determine the proper method for monitoring CSOs.
- Table 4 displays various methods used to estimate CSO volumes.

Position	Technique	Features	Main drawbacks
	Stage-discharge relation	Pre-designed device	Need for specific
	methods		hydraulic conditions
Overflow channel	Stage-discharge relation	On-site calibration	Site-dependent
	methods		
	Velocity based methods	-	Representativeness
	Stage-discharge relation	Pre-designed device	Need for specific
Main abannal	methods		hydraulic conditions
(upstroom &	Stage-discharge relation	On-site calibration	Site-dependent
(upsueant &	methods		
the CSO)	Velocity based methods	-	Representativeness
life CSO)		-	Double equipment
	-	-	Indirect measurement
	Stage-discharge relation	Classical geometry	Need for specific
CSO shambar	methods		hydraulic conditions
	Stage-discharge relation	On-site calibration	Site-dependent
	methods		

Table 4. CSOs measurement methods (adopted from Maté Marín et al., 2018).

390 Sensors and probes are also applied for monitoring purposes in most of the high income

391 countries, such as conductivity meters to detect occurrence and determine duration, level sensors

392 with moderate and/or higher cost, advanced sensors (eg UV-VIS) for also determining water

quality. Where budget is limited, level sensors can be coupled with overflow equations to

measure CSO volume. On the other hand, a level and a velocity sensor combined with

flowmeters generate the most accurate/reliable data but require more investment cost and higher
maintenance (Montserrat et al., 2013).

The costs of data storage and high capacity computer systems are still an issue in CSO monitoring. Moreover, in heavy rain events, huge quantities of data must be processed and evaluated for every alarm situation in order to take immediate action (Bailey et al., 2016). The other point is the location of the CSO control system. The characteristics of the land can make the connection to the network difficult.

A low-cost method was introduced by Montserrat et al. (2013) to detect the occurrence and 402 403 duration of CSO events. The proposed method depends on the temperature changes between the sewer gas phase and the overflowing mixture of wastewater and storm water. Using temperature 404 sensors for CSO detection has several advantages such as minimum capital cost, easy installation, 405 406 requirement of minimum technical knowledge for integration, tolerance to extreme environmental conditions and minimum maintenance. The authors also validated their systems 407 and achieved detection greater than 80% of the total CSO occurrences, which showed that 408 temperature differentiation during seasonal changes does not have a negative impact on 409 effectiveness. However, physical features of the weir affect the detection performance. Later 410 research, published in 2018, increased the robustness of the method proposed in Montserrat et al. 411 412 (2013) by adding a second temperature sensor, improving the detection accuracy by implementing an algorithm that accounted for the response time of the system and automatically 413 414 calculated the duration of CSO events (Hofer et al., 2018). As a result, in a 7-month test phase, all 415 20 CSO events were recognised without false detections. Another group from France, recently developed a system called the DSM-flux (Device for Storm 416

417 water and combined sewer flows Monitoring and the control of pollutant fluxes) to determine and

control both the quantity and quality of CSO discharges (Maté Marín et al., 2018). The validated
system can measure overflow volumes and pollutant concentration, decrease particulate
pollutants from sedimentation and the erosive potential of overflows to the receiving waters. The
advantages of installation of the DSM-flux system are: - direct measurement at the overflow
channel, - installation downstream from the existing CSO structure, -requirement of only one
level measurement for determination of discharge values, - not affected by inlet hydraulic
conditions, - reduced particulate pollutants and erosive potential of CSO discharges.

425 5.1. Smart CSO monitoring and control

426 Currently smart network monitoring and smart data infrastructures (US EPA, 2018) are under development and application. These infrastructures are implemented in connection with a 427 supervisory control and data acquisition (SCADA) system and are mainly focused on real-time 428 429 monitoring of flow rates (physically or with alternative methods) and effluent levels of CSO's with the aim of assessing potential flooding and pollution incidents. The final objective is to 430 support decisions in real-time or quasi real-time about actions to be taken. For instance, SPRINT 431 226 a European project focused on the implementation of real-time sewer system control for 432 eight European cities: Copenhagen (Denmark), Mantova (Italy), Verona (Italy), Genoa(Italy), 433 Berlin (Germany), Vitoria-Gasteiz (Spain), Bolton (United Kingdom), and Goteborg (Sweden) 434 (Entem, Lahoud, Yde, & Bendsen, 1998). The project showed decent real-time control 435 performance for overflow events of the sewer system in terms of prediction and generation of 436 437 strategies to be taken into consideration (Entern et al., 1998). Another study (Seggelke et al., 438 2013) focused on real-time control of a CSS in a city in Germany with the aim of monitoring 439 frequency of overflow events and investigating how to reduce them. In addition, Carbone et al., 440 2014 investigated a real-time control solution for an urban drainage network in Italy. It used an

innovative and smart series of gates that automatically adjusted themselves in order to optimize 441 the storage capacity of a sewer system during rainfall events. Moreover, in the INTCATCH 442 project, as an innovative approach to monitor water quality, autonomous and radio controlled 443 444 boats are developed and demonstrated in key catchments such as Lake Garda, Lake Yliki (Warner, Nödler, Farinelli, Blum, & Licha, 2018). The results revealed that monitoring the 445 routine parameters can give an overview of the current status of the water body, as well as 446 447 contribute to reducing the monitoring cost. Moreover, real-time monitoring of site-specific indicator allows determining the pollutant source which helps to derive proper catchment 448 management strategy (Warner et al., 2018). The applications of smart data infrastructure systems can be 449 450 optimized by two different methods. Whereas the system improvements refer to increasing weirs, optimizing the efficiency curves or location of CSO control, the real-time control systems manage the operation of wastewater 451 networks and facilities in real time (US EPA, 2018Grey (such as large concrete tanks or tunnels) 452 and green strategies (such as bioretention facilities, green roofs, porous pavements, and 453 stormwater planters) can be applied to control CSOs (De Sousa, Montalto, & Spatari, 2012) and 454 hybrid system of grey and green methods more advantageous than grey method-only in terms of 455 economy, environment and society (Gong et al., 2019). The control strategies can be optimized 456 by hydrological model simulations supported with scenario analyses (Chen et al., 2019). In the 457 USA, different approaches are integrated in different states to control and manage CSOs. In 458 Philadelphia, the Water Department has a goal to reduce overflows (7.9 billion gallons of 459 overflow water) by 2036. For this purpose, smart data technology was integrated into existing 460 461 stormwater retention basins to monitor basin water level and precipitation, and maximize the 462 performance of the basin by real-time active control to selectively discharge from the basin during optimal times. On the other hand, 10 high frequency cleanout sites with remote field 463 464 monitoring units were integrated in the San Antonio Water System (SAWS) in which day-to-day

level trend changes can be detected by an analytical software giving data for potentially 465 important changes in water levels. In the pilot locations, there were no sewer overflows in 466 May/June 2016 with when nearly 16 inches of rain overwhelmed the SAWS. The real-time 467 468 control system was adopted in Louisville in 1990s and actively used since 2006. The system prevents more than 1 billion gallons of CSO volume annually. In Indiana, there are 152 sensors 469 located through the city of South Bend to maximize the capacity and performance of the city's 470 collection system, which helped to reduce total CSO volume by roughly 70 percent, or about 1 471 billion gallons per year during the period 2008-2014. Moreover, in Greater Cincinnati, there are 472 more than 200 CSO points, causing a discharge over 11 billion gallons of sewage into the Ohio 473 River and its tributaries annually. 164 overflow points were integrated within the frame of the 474 smart sewers network to date and sensors were installed through the watershed (USEPA, 2018). 475 The monitoring technology should be pursued in the catchment base, and economical analysis 476 should be carefully proceed to decide to integrate the best smart strategy. 477

478

5.2. Innovative treatment alternatives

Different strategies are developed to reduce the impacts of CSOs, such as increasing storage capacity, detention/retention facilities, as well as sewer separation to fulfill the requirements of the related regulations (Figure 2). However, converting CSS into a separated system can be prohibitive due to cost and it does not always guarantee pollution reduction (Li et al., 2010). One of the many goals of this review is to gather the latest information on treatment technologies, grouped as natural and technological treatment, and their performances in treating CSOs.

485 Treatment alternatives are summarized in Table 5.

486 Table 5. Studies with different treatment alternatives for (CSOs
---	------

Treatment	Location	System	Purpose	Target	Reference
	Gorla Maggiore, Italy	Vertical flow subsurface beds (VF) as first stage and a free water surface bed (FWS) as second stage	Flow reduction	Flow reduction: 86.2%	Rizzo et al. (2018)
	Germany	Retention soil filters (RSFs)	CPOD, TSS and P	COD removal: 49% TSS removal: 38% Phosphorous removal: 34%	Tondera et al. (2017)
Natural Treatment	Gorla Maggiore, Italy	Vertical flow subsurface beds (VF) as first stage and a free water surface bed (FWS) as second stage	COD and NH ₄ ⁺	COD removal: 87% NH ₄ ⁺ removal: 94%	Masi et al. (2017)
	Tettnang, Germany	RSFs	Micropollutants and pathogenic/antibiotic resistant bacteria	COD removal: 80 ± 10% E. coli removal: 2.7 log-units Enterococci removal: 2.2 log-units	Scheurer et al (2015)
	Carrión de los Céspedes, Spain	Vertical flow CW + horizontal flow CW + Free water surface CW	TSS and disinfection	TSS removal: $90 \pm 8\%$ disinfection efficiency :4.7 logarithmic units CFU/100 mL for E. coli	Ávila et al. (2013)
	Pilot –scale experiment	Activated soil filter	Biocides and biocide metabolites removal	Dry weather conditions: Removal rates: 80-100% High flow conditions: Triazines: 50-70% Phebylureas: 16-100% DCOIT: 99-100% BIT: 72-96% IPBC: 43%	(Bester et al., 2011)
	Pilot-scale experiment	Activated soil filter	Organic micro-pollutant removal	Lipophilic compounds removal: 64-99% Persistent hydrophilic compounds removal: 0-95% depending on the	(Bester & Schäfer, 2009

				operation period	
	Boudonville, France	Coagulation with ferric chloride solution (CLARFER), aluminum salts (WAC HB)	TSS and heavy metals	Turbidity removal: >86%	El Samrani et al. (2008)
	Seine Aval plant, France	Ballasted flocculation unit	TSS, POC, COD, P	TSS removal: 86.7% -80.2% POC removal: 84.8% -77.5% COD removal: 75.2% -76.8% P _{tot} removal: 86.4% - 88.4% Hydrophilic compound removal: 20% - 50%	Gasperi et al. (2012)
	Germany	Adsorption: Biochar	Specific pollutants	Acetaminophen removal: 94.1% Naproxen removal: 97.7 %	Jung et al. (2015)
	Simulated CSO with real wastewater	Activated soil filter (Bio filter)	TOC and micro pollutants	Hydrophilic markers: 81-98% Lipophilic markers: 30-99% TCPP: 64% TOC removal: >50%	Bester and Schäfer (2009)
treatment	Kærby, Denmark	PAX dosing point before the HydroSeparator followed by a dosing point for PAA + CW	TSS, P, disinfection	Turbidity removal: 89.8% Phosphate removal: 26.6% Enterococcus removal: 1.3-3.5 log	Chhetri et al. (2016)
	Synthetic CSO	The adsorption and photo-reduction-a composite catalyst of TiO ₂ and Graphene	Zn ²⁺	Zn^{2+} removal: 20.3 \pm 0.04% increase	Kumordzi et al. (2016)
	North Rhine- Westphalia, Germany	Performic acid	Disinfection	<i>Aeromonas</i> spp. reduction: 1.8 log <i>E. coli.</i> reduction: 3.1 log Somatic coliphages reduction: 2.7 log	Tondera et al. (2016)
	Synthetic sanitary sewer overflow	Biofilter	BOD ₅ and TSS	BOD ₅ removal: 84 ± 9% TSS removal: >90%	Tao et al. (2010)
	Synthetic CSO	Disinfection by PFA and acid PAA	Disinfection	<i>E.coli</i> reduction: ~3 log units <i>Enterococcus</i> reduction: ~3 log	Chhetri et al. (2014)
	Synthetic CSO	Disinfection by PAA	Disinfection	Full disinfection at pH 8.5	McFadden et al.

	and hypochlorite			(2017)
Ruhr, Germany, simulated CSO	UV disinfection and ozonation	Disinfection	<i>E.coli</i> reduction: 2.2-3.5 log Coliform bacteria reduction: 1.7- 3.3 log	Tondera et al. (2015)
	UV disinfection with coagulation	UV transmission	Increase on UVT: 78%	Gibson et al. (2016)
Lake Garda, Italy	A dynamic rotating belt filter, adsorption on granular activated carbon and UV disinfection	TSS, COD and <i>E. coli</i> removal	TSS removal: >90% COD removal: >69% E. coli removal: >99%	Botturi et al. (2020)

488 5.2.1. Natural extensive treatment

Green infrastructure and nature-based solutions (NBS) use natural processes to contribute to the improved, sustainable management of water as well as enhancing natural capital and biodiversity. Green infrastructure is recognized to deliver multiple benefits by combining continuous treatment of CSOs with additional services in terms of flood protection, increased biodiversity, climate change resilience and recreational activities.

There is growing recognition that green infrastructure are flexible, multi-purpose alternatives to 494 495 traditional, often costlier treatment solutions that can be applied in diverse wastewaters (Vymazal, 2011) including treatment of residential, municipal and agricultural storm water and 496 wastewater and urban run-off. They are incorporated into and promoted in Europe by the 497 European Commission Strategy on Green Infrastructure (EC, 2013) and in the UK; an example is 498 the London Environment Strategy (GLA, 2018). Green infrastructure is therefore an increasingly 499 important possible solution for pollution mitigation. As well as being an environmentally friendly 500 alternative, green infrastructure are flexible in terms of size, cost-effective and have a discrete 501 layout (Fu, Goddard, Wang, & Hopton, 2019). Of the green infrastructure techniques, constructed 502 503 wetlands (CW) have a long history of wastewater treatment and have many applications for CSO treatment (Levy, Smardon, Bays, & Meyer, 2014; Masi et al., 2017; Pálfy et al., 2018, 2016; 504 Rouff, Eaton, & Lanzirotti, 2013; Tondera, 2017). The largest number of constructed wetlands 505 506 for combined sewer overflow treatment (CSO-CW) exist in Germany, where the first large-scale treatment plants were implemented in the early 1990. In North-Rhine Westphalia alone, a state 507 with approx. 18 million inhabitants, more than 150 facilities exist with a treatment capacity of 508 100 to 36,000 m³ (site currently under construction) per rainfall event. The newly released 509 national guideline (DWA, 2019) describes design, construction and maintenance of the system. In 510

511	principal, pre-settled combined sewage is distributed on a vegetated filter body with a sand layer
512	of 0.75 cm. A ponding zone allows temporary storage of up to 2 m^3 per m^2 water and the outflow
513	is throttled and ideally does not open before full saturation of the filter body has been reached.
514	The filter material consists of engineered media ('technical sand', $0/2$ mm). The required capacity
515	is based on ten-year rainfall simulations and the sensitivity of the surface waterbody.
516	Investigations of these systems, especially in the last 15 years, show a total suspended solid
517	(TSS) removal of >90%, chemical oxygen demand (COD) removal of >80%, a high nitrification
518	potential (ammonium removal of >60% depending on inflow concentrations and preceding dry
519	period), bacterial removal of 1 to 3 log_{10} , but also removal of certain micropollutants
520	(Christoffels et al., 2014; Scheurer et al., 2015; Tondera, 2017; Tondera et al., 2013; Tondera,
521	Ruppelt, Pinnekamp, Kistemann, & Schreiber, 2019). Phosphate and heavy metals can be
522	reduced until the overall sorption capacity of the filter body has been reached; an increase is
523	possible by adding adsorptive materials or implementing post-filter steps.
524	The layout has been adapted in research projects in France and Italy (Meyer et al., 2013). Masi et
525	al. (2017) describes the Italian approach implemented at Gorla Maggiore (Table 5). The system
526	was designed to treat the first flush of the overflow via vertical-flow wetlands, whereas the later
527	occurring, higher diluted overflow is bypassed into a free water surface wetland. During the study
528	period, 69 CSO events happened and the system successfully reduced the COD concentration by
529	87% and NH ₄ concentration by 93%. As additional benefit, the construction mitigates flood risk.
530	Rizzo et al. (2018) describes the Italian approach and shows that the system reduced the effects of
531	CSOs in the river by smoothing peak loads and contributing to improved water quality.
532	Similarly, Ávila et al. (2013) demonstrated the function of a pilot-scale treatment system
533	consisting of a vertical subsurface flow, a horizontal subsurface flow and a free water surface
534	constructed wetland for the treatment of effluent from a combined sewer and results showed

efficient performance in terms of organic carbon and TSS removal under dry weather conditions.
As expected, during the storm events there were a prompt increase in carbon and TSS load for a
short period followed by a dilution effect.

538 5.2.2. Technological compact treatment

Minimizing the negative impact of CSOs in the receiving waters can be achieved by in-line 539 treatment methods such as settling without additives, which is the most commonly applied 540 method, and chemical coagulation before discharge. Coagulation and flocculation are an effective 541 method to remove organic materials with organic/inorganic polymers as coagulants and 542 543 flocculants to get better sedimentation. In a study carried out by El Samrani et al. (2008), effects of different commercial coagulants - namely, ferric chloride solution (CLARFER) and aluminum 544 salts (WAC HB) - were evaluated on turbidity and heavy metal removal from samples collected 545 546 during rainy weather at the inlet of Boudonville retention basin. The results showed that both coagulants provided excellent removal of heavy metals; indeed; the concentrations of Cu, Zn and 547 Pb in the treated water complied with the water legislation. 548

Regarding flocculation treating CSOs, Gasperi et al. (2012) examined the performance of a full-549 550 scale ballasted flocculation unit (BFU) implemented at the bypass of the wastewater treatment plant located downstream of Paris on the Seine River. Ferric chloride (FeCl₃) and anomic 551 552 polymer were respectively used as coagulant and flocculant according to the turbidity levels entering BFU, and high surface area was achieved by microsand to enhance flocculation, assist 553 554 flock formation and act as ballast, which aids rapid settlement. The performance of the system 555 was evaluated during the wet period, in which the bypassed combined sewage was treated only with BFU and bio-filtration in order to remove nitrogen, before discharge. Significant removal 556 rates (>80%) were achieved for the compounds with a strong hydrophobic character (log Kow > 557

5.5) and removal rates of 50-80% were achieved for intermediate hydrophobic compounds (4 <
log Kow < 5.5). On the other hand, low hydrophobic compounds (log Kow < 4) were poorly
(<20%) to weakly removed (<50%). The authors concluded that it is a promising process to treat
CSO waters in order to remove various compounds.

Another possibility to remove very small particles or dissolved substances especially is by 562 adsorption. Although (Jung et al., 2015) investigated positive removal of micropollutants such as 563 acetaminophen and naproxen (94.1 and 97.7 %, respectively) from artificial combined sewage 564 565 with biochar in a lab scale study, there is no application on a large scale yet, since removing the adsorbent from the wastewater matrix is difficult. Easier is the combination of a sand filter or 566 vertical-flow constructed wetland containing an activated layer; such as investigated by Bester & 567 Schäfer (2009). They evaluated the performance of an activated soil filter (bio filter) in order to 568 eliminate diverse xenobiotics from combined sewage, storm water and wastewater. The results 569 indicated that the removal efficiency of organic micropollutants depends on the application of an 570 organic layer in the filter, enabling higher removal efficiency. In a comprehensive study of 571 sanitary sewer overflow treatment with fixed media biofilters, results showed that, all bioreactors 572 can remove TSS, ammonia and phosphorous effectively (Tao, Mancl, & Tuovinen, 2010). 573 Moreover, BOD₅ reduction efficiency of $84 \pm 9\%$ can be reached with sand bioreactors. In 574 another study Kumordzi et al. (2016) focused on to remove the most abundant heavy metal, 575 namely Zn^{2+} , in simulated CSOs by a composite catalyst of TiO₂ and Graphene under various 576 process conditions such as pH, light intensity, catalyst loading and light source in a lab-scale 577 system. The adsorption and photo-reduction of Zn²⁺ enhanced with TiO₂-G under the solar 578 spectrum. On the other hand, adsorption is not the best solution in case of high clogging risk and 579 580 water volume.

Rotating belt filter is another option for CSO treatment in terms of their minimal footprint and
also easier implementation. (Gutierrez, 2015).

Within the scope of INTCATCH Horizon2020 Innovation funded European project, a demo 583 plant, with the aim of treating CSOs before their discharge into Garda Lake, was installed at Villa 584 Bagatta. Additional aims considered the concept of technological innovation and public 585 participation in integrated and smart management of water infrastructure and basins (Figure 3). 586 587 The pilot plant has a compact modular design, composed of three main sections; rotating belt filtration (RBF), filtration on granular activated carbon (GAC) and disinfection by UV treatment 588 (Figure 4). Despite the fact that the processes used in this project used for decades for wastewater 589 treatment, they have not been applied specifically for the treatment of CSO discharges. 590 The plant can treat 54 m³/h. The Rotating Dynamic Filter (Salsnes Filter, SF1000) accomplished 591 the sieving of the CSOs through a mesh size of 350 µm and the retained solids are thickened 592 using an embedded screw-press unit, achieving a total solid concentration of 20-35%. The outlet 593 CSOs is stored in an existing concrete open tank where it may be pumped up to $3.6 \text{ m}^3/\text{h}$ to the 594 GAC filtration system. Following the GAC system, is an ultraviolet disinfection unit with 4 595 modules (Trojan Technologies, UV3400K) installed in the open channel. Electrical conductivity, 596 pH, and multiple parameters simultaneously derived by UV/Vis optical spectrometry (Intelligent 597 598 Spectral Analyser (ISA)) are installed to monitor the system. Data are gathered and transmitted to cloud computing which is also integrating sustainability evaluation and assessment tools in order 599 to provide eco-efficiency indicators of the treatment and management system. The plant reached 600 satisfactory removal efficiencies for TSS (90%), COD (69%) and E. coli (%99). However, further 601 treatment is required for efficient nutrient removal in which TN and TP removal of around 41% 602 and 19%, respectively (Botturi et al., 2020). The innovations of this project are its modular 603 structure, compactness, rapid treatment and resilience of the system which enables to re-shape of 604

605 the configuration according to the treatment requirements.

606	To sustain the safety of the water quality of receiving water bodies used for recreational
607	purposes, microbial loads from CSOs should be reduced. Since quality and quantity of CSOs are
608	very variable, it a challenge to find suitable disinfection technologies which can be operated
609	spontaneously for a short period at full capacity. The most commonly applied disinfection
610	methods for the treatment of WWTP effluent are using chlorine compounds, ozone and ultra-
611	violet (UV). However, these are not ideal for CSO treatment due to the high concentrations of
612	solids and dissolved organic compounds: using chlorine compounds can lead to the formation of
613	toxic, mutagenic and carcinogenic chlorinate by-products (Bayo, Angosto, & Gómez-López,
614	2009; Nurizzo, Antonelli, Profaizer, & Romele, 2005).
615	Undesirable by-products can also be the result when using ozone. Tondera et al. (2015) evaluated
616	the effects of ozonation on diluted wastewater in a pilot scale application. Although the reduction
617	of pathogenic bacteria, viruses, and protozoan parasites were promising and more effective than
618	UV irradiation for the tested conditions, the operation of an ozone generator under these
619	conditions is difficult to manage and both installation and operation is costly.
620	Suspended solids and turbidity in CSOs are also limiting parameters on the disinfecting effects of
621	UV radiation (Tondera et al., 2015). In another study, Gibson et al. (2016) evaluated the effects
622	of chemical pre-treatment of CSOs for subsequent UV disinfection. When applying 20 mg/L
623	alum, the UV light transmission of the raw CSO increased from 30 to 60% after settling. The
624	high charge density cationic polymer improved the removal of turbidity but did not affect UV
625	transmittance (UVT) and TSS. The use of alum (metal coagulants) can achieve a UVT of 78%,
626	while the use of cationic polymers reached a value of 60%. Pre-treatment to remove particles via
627	CSO-CWs, as described above, not only increases the removal of microbial loads, but also

allows reduction of dissolved parameters. In addition, no chemical addition is required, but space
availability and installation costs are critical.

Alternative treatment with peroxy acids was investigated in several recent studies. Peracetic acid

(PAA) requires a reaction time of several hours (Chhetri et al., 2014). The influence of particles 631 on the removal efficiency gave controversial results: While Chhetri et al. (2016) found that 632 bacterial reduction was more mostly efficient with a pre-treatment by particle separator and an 633 additional coagulation with poly-aluminum-chloride, McFadden et al. (2017) could not find an 634 635 effect of particle removal on the efficiency of CSO treatment with PAA. As an alternative to PAA, performic acid (PFA) requires only a short contact time Under real 636 scale conditions, Chhetri et al. (2015) showed a reduction of 2.0 log₁₀ of Escherichia coli and 1.3 637 log₁₀ of intestinal enterococci (contact time of 20 min, 8 mg l-1 min-1 reduced approximately), 638 and Tondera et al. (2016) proved additional reduction of coliform bacteria, Aeromonas spp. and 639 P. aeruginosa with a log₁₀ reduction between 1.8 and 2.9 (contact time of max. 30 min, 12 to 24 640 mg l⁻¹ min⁻¹). Additionally, a reduction of somatic coliphages with $2.7 \pm 1.7 \log_{10}$ could be 641 shown. Another advantage of using PFA is that the commercially available reaction chamber 642 providing PFA seems to be tolerant to long standstills, which can occur during dry seasons 643 without CSOs. 644

645 **6. Economics**

630

Municipalities should invest in infrastructures to monitor, control and treat CSOs to meet regulatory obligations of the receiving water bodies. It should be noted that the private companies can also involve in the controlling of sewerage systems besides the government. Since legislations are encouraged to apply better management strategies for CSO discharges, there are no strict regulations. Thus, CSO discharge management is still an issue.

Real time control systems seem a cost effective alternative since they only require additional 651 implementations to the existing systems. The design step is crucial to select the right equipment 652 with the proper communication system and software, which may lead to significant capital 653 investment costs. In real time control systems, cleaning equipment needs to be integrated into the 654 instrumentation to prevent, fouling of the sensors. While, these integrations increase the capital 655 costs, they have an advantage in the long term of reduced maintenance costs (Campisano, Cabot 656 657 Ple, Muschalla, Pleau, & Vanrolleghem, 2013). Colas et al., (2004) summarized the benefits of real time controlling on CSOs for different locations. In Paris, the capital cost of CSO controlling 658 was reduced by almost 25% by application of real-time control to the system. In Louisville, the 659 municipality has reduced the cost of CSO long-term control program by \$150 million by 660 integrating a real-time controlling system. In another application in Quebec, \$90 million was 661 saved in the capital cost to the Quebec City CSO Control Program in terms of reducing the 662 number and the size of some facilities. In Berlin €90 million was invested to reduce CSO's, in 663 which the cheapest measures are real time controlling inside the CS. On the other hand, 664 construction of retention basins cost 1000€/m³. An external basin has been tested in Berlin's 665 River Spree since 2011 but at the end costs were not lower than for underground structures. In 666 Ancona and Falconara Marittima (Italy) \in 22 million have been planned to be invested for CSO 667 668 management.

Different technologies and approaches can be integrated and/or applied for CSO controlling.
During the decision, the optimum method should be evaluated based on the physical properties of
the interface, applicability of the technology, operational & maintenance costs, cost-benefit ratio.

672 **7. Conclusions and further research needs**

673 CSO discharge is still a major environmental threat that need to be better monitored to provide

data-driven decision support towards water infrastructure upgrading. Although, the negative 674 impacts of CSO discharges on aquatic environments are defined extensively, strict limitations are 675 still needed to be set in the national regulations to force water managers taking necessary actions. 676 To date, several cost-efficiency real-time monitoring systems are available and innovation 677 projects are even using cloud and IoT platforms to better engage stakeholders and citizens and 678 raise awareness about the CSO management importance. A combination of NBS and compact 679 680 treatment system coupling smart monitoring with green and gray eco-innovative solutions should be planned at catchment scale, depending on the best technical, environmental and economic 681 sustainability. Modular structures of these systems enable to set up different configurations 682 according to the treatment requirements and field features. Moreover, extensive research is 683 needed to validate actual integrated actions at catchment scale, integrating novel low-cost 684 sensors, innovative treatment technologies, digital platforms and eco-efficiency assessment. 685 Further researches and monitoring experiences will support the development of future concrete 686 guidelines and strategies to manage the CSOs and to mitigate their impacts on the environment. 687

688 Conflict of interest

689 The authors have declared no conflict of interest.

690 Acknowledgements

⁶⁹¹ The authors acknowledge the European Union's Horizon2020 research and innovation

⁶⁹² programme for co-funding INTCATCH innovation action under grant agreement No.689341.

693 **References**

Al Aukidy, M., & Verlicchi, P. (2017). Contributions of combined sewer overflows and treated
 effluents to the bacterial load released into a coastal area. *Science of the Total Environment*,

696	607-608, 483-496. https://doi.org/10.1016/j.scitotenv.2017.07.050
697	ATV-128. (1992). Standards for the Dimensioning and Design of Stormwater Structures in
698	Combined Sewers.
699	Ávila, C., Salas, J. J., Martín, I., Aragón, C., & García, J. (2013). Integrated treatment of
700	combined sewer wastewater and stormwater in a hybrid constructed wetland system in
701	southern Spain and its further reuse. Ecological Engineering, 50, 13–20.
702	https://doi.org/10.1016/j.ecoleng.2012.08.009
703	Bailey, J., Harris, E., Keedwell, E., Djordjevic, S., & Kapelan, Z. (2016). The Use of Telemetry
704	Data for the Identification of Issues at Combined Sewer Overflows. Procedia Engineering,
705	154, 1201-1208. https://doi.org/10.1016/j.proeng.2016.07.524
706	Bayo, J., Angosto, J. M., & Gómez-López, M. D. (2009). Ecotoxicological screening of
707	reclaimed disinfected wastewater by Vibrio fischeri bioassay after a chlorination-
708	dechlorination process. Journal of Hazardous Materials, 172(1), 166-171.
709	https://doi.org/10.1016/j.jhazmat.2009.06.157
710	Bester, K., Banzhaf, S., Burkhardt, M., Janzen, N., Niederstrasser, B., & Scheytt, T. (2011).
711	Activated soil filters for removal of biocides from contaminated run-off and waste-waters.
712	Chemosphere, 85(8), 1233–1240. https://doi.org/10.1016/j.chemosphere.2011.07.017
713	Bester, K., & Schäfer, D. (2009). Activated soil filters (bio filters) for the elimination of
714	xenobiotics (micro-pollutants) from storm- and waste waters. Water Research, 43(10),
715	2639–2646. https://doi.org/10.1016/j.watres.2009.03.026
716	Birch, H., Mikkelsen, P. S., Jensen, J. K., & Holten Lützhøft, H. C. (2011). Micropollutants in
717	stormwater runoff and combined sewer overflow in the Copenhagen area, Denmark. Water

718	Science and Technology, 64(2), 485-493. https://doi.org/10.2166/wst.2011.687
719	Botturi, A., Daneshgar, S., Cordioli, A., Foglia, A., Eusebi, A. L., & Fatone, F. (2020). An
720	innovative compact system for advanced treatment of combined sewer overflows (CSOs)
721	discharged into large lakes : Pilot-scale validation. Journal of Environmental Management,
722	256(September 2019), 109937. https://doi.org/10.1016/j.jenvman.2019.109937
723	Brzezińska, A., Zawilski, M., & Sakson, G. (2016). Assessment of pollutant load emission from
724	combined sewer overflows based on the online monitoring. Environmental Monitoring and
725	Assessment, 188(9). https://doi.org/10.1007/s10661-016-5461-6
726	Buerge, I. J., Poiger, T., Müller, M. D., & Buser, H. R. (2006). Combined sewer overflows to
727	surface waters detected by the anthropogenic marker caffeine. Environmental Science and
728	Technology, 40(13), 4096–4102. https://doi.org/10.1021/es0525531
729	Campisano, A., Cabot Ple, J., Muschalla, D., Pleau, M., & Vanrolleghem, P. A. (2013). Potential
730	and limitations of modern equipment for real time control of urban wastewater systems.
731	Urban Water Journal, 10(5), 300-311. https://doi.org/10.1080/1573062X.2013.763996
732	Chen, J., Liu, Y., Gitau, M. W., Engel, B. A., Flanagan, D. C., & Harbor, J. M. (2019).
733	Evaluation of the effectiveness of green infrastructure on hydrology and water quality in a
734	combined sewer overflow community. Science of the Total Environment, 665, 69–79.
735	https://doi.org/10.1016/j.scitotenv.2019.01.416
736	Chhetri, R. K., Flagstad, R., Munch, E. S., Hørning, C., Berner, J., Kolte-Olsen, A., Andersen,
737	H. R. (2015). Full scale evaluation of combined sewer overflows disinfection using
738	performic acid in a sea-outfall pipe. Chemical Engineering Journal, 270, 133–139.
739	https://doi.org/10.1016/j.cei.2015.01.136

740	Chhetri, R. K., Thornberg, D., Berner, J., Gramstad, R., Öjstedt, U., Sharma, A. K., & Andersen,
741	H. R. (2014). Chemical disinfection of combined sewer overflow waters using performic
742	acid or peracetic acids. Science of the Total Environment, 490, 1065–1072.
743	https://doi.org/10.1016/j.scitotenv.2014.05.079
744	Christoffels, E., Mertens, F. M., Kistemann, T., & Schreiber, C. (2014). Retention of
745	pharmaceutical residues and microorganisms at the Altendorf retention soil filter. Water
746	Science and Technology, 70(9), 1503–1509. https://doi.org/10.2166/wst.2014.404
747	De Sousa, M. R. C., Montalto, F. A., & Spatari, S. (2012). Using Life Cycle Assessment to
748	Evaluate Green and Grey Combined Sewer Overflow Control Strategies. Journal of
749	Industrial Ecology, 16(6), 901-913. https://doi.org/10.1111/j.1530-9290.2012.00534.x
750	Del Río, H., Suárez, J., Puertas, J., & Ures, P. (2013). PPCPs wet weather mobilization in a
751	combined sewer in NW Spain. Science of the Total Environment, 449, 189–198.
752	https://doi.org/10.1016/j.scitotenv.2013.01.049
753	DWA. (2013a). Arbeitsblatt DWA-A 166: Bauwerke der zentralen 2 Regenwasserbehandlung
754	und-rückhaltung - Konstruktive Gestaltung und 3 Ausrüstung. Deutsche Vereinigung für
755	Wasserwirtschaft, Abwasser und Abfall 4 e.V. Hennef, Germany.
756	DWA. (2013b). Merkblatt DWA-M 176: Hinweise zur konstruktiven Gestaltung und Ausrüstung
757	von Bauwerken der zentralen Regenwasserbehandlung und -rückhaltung. Deutsche
758	Vereinigung für Wasserwirtschaft, Abwasser und Abfall e.V. Hennef, Germany.
759	EC. (2013). European Commission Strategy on Green Infrastructure, Communication from the
760	Commission to the European Parliament, The Council, The European Economic and Social
761	Committee and Committee of the Regions.

762	El Samrani, A. G., Lartiges, B. S., & Villiéras, F. (2008). Chemical coagulation of combined
763	sewer overflow: Heavy metal removal and treatment optimization. Water Research, 42(4-5),
764	951–960. https://doi.org/10.1016/j.watres.2007.09.009
765	Entem, S., Lahoud, A., Yde, L., & Bendsen, B. (1998). Real time control of the sewer system of
766	boulogne billancourt - a contribution to improving the water quality of the seine. Water
767	Science and Technology, 37(1). https://doi.org/10.1016/S0273-1223(97)00785-3
768	EU. (2006). Regulation (EC) No 166/2006 of the European Parliament and of the Council of 18
769	January 2006 Concerning the Establishment of a European Pollutant Release and Transfer
770	Register and Amending Council Directives 91/689/EEC and 96/61/EC, 166/2006.
771	EurEau. (2016). Overflows from collecting systems, 32(May), 1-6. Retrieved from
772	www.eureau.org
773	Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify
773 774	Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i> , 39(23),
773 774 775	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, 39(23), 9244–9252. https://doi.org/10.1021/es047965t
773 774 775 776	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based
773 774 775 776 777	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows
773 774 775 776 777 778	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows (CSOs). <i>Journal of Environmental Management</i>, <i>236</i>(August 2018), 571–580.
773 774 775 776 777 778 779	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows (CSOs). <i>Journal of Environmental Management</i>, <i>236</i>(August 2018), 571–580. https://doi.org/10.1016/j.jenvman.2018.12.089
773 774 775 776 777 778 779 780	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows (CSOs). <i>Journal of Environmental Management</i>, <i>236</i>(August 2018), 571–580. https://doi.org/10.1016/j.jenvman.2018.12.089 Gasperi, J, Sebastian, C., Ruban, V., Delamain, M., Percot, S., Wiest, L., & Mirande, C. (2014).
773 774 775 776 777 778 779 780 781	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows (CSOs). <i>Journal of Environmental Management</i>, <i>236</i>(August 2018), 571–580. https://doi.org/10.1016/j.jenvman.2018.12.089 Gasperi, J, Sebastian, C., Ruban, V., Delamain, M., Percot, S., Wiest, L., & Mirande, C. (2014). Micropollutants in urban stormwater : occurrence , concentrations , and atmospheric
773 774 775 776 777 778 779 780 781 782	 Fono, L. J., & Sedlak, D. L. (2005). Use of the chiral pharmaceutical propranolol to identify sewage discharges into surface waters. <i>Environmental Science and Technology</i>, <i>39</i>(23), 9244–9252. https://doi.org/10.1021/es047965t Fu, X., Goddard, H., Wang, X., & Hopton, M. E. (2019). Development of a scenario-based stormwater management planning support system for reducing combined sewer overflows (CSOs). <i>Journal of Environmental Management</i>, <i>236</i>(August 2018), 571–580. https://doi.org/10.1016/j.jenvman.2018.12.089 Gasperi, J, Sebastian, C., Ruban, V., Delamain, M., Percot, S., Wiest, L., & Mirande, C. (2014). Micropollutants in urban stormwater : occurrence , concentrations , and atmospheric contributions for a wide range of contaminants in three French catchments. <i>Environmental</i>

784 2396-0

785	Gasperi, Johnny, Laborie, B., & Rocher, V. (2012). Treatment of combined sewer overflows by
786	ballasted flocculation: Removal study of a large broad spectrum of pollutants. Chemical
787	Engineering Journal, 211-212(2012), 293-301. https://doi.org/10.1016/j.cej.2012.09.025
788	Gasperi, Johnny, Zgheib, S., Cladière, M., Rocher, V., Moilleron, R., & Chebbo, G. (2012).
789	Priority pollutants in urban stormwater: Part 2 - Case of combined sewers. Water Research,
790	46(20), 6693-6703. https://doi.org/10.1016/j.watres.2011.09.041
791	Gibson, J., Farnood, R., & Seto, P. (2016). Chemical pretreatment of combined sewer overflows
792	for improved UV disinfection. Water Science and Technology, 73(2), 375–381.
793	https://doi.org/10.2166/wst.2015.447
794	Gong, Y., Chen, Y., Yu, L., Li, J., Pan, X., Shen, Z., Qiu, Q. (2019). Effectiveness analysis of
795	systematic combined sewer overflow control schemes in the sponge city pilot area of
796	Beijing. International Journal of Environmental Research and Public Health, 16(9), 1–18.
797	https://doi.org/10.3390/ijerph16091503
798	Gutierrez, M. (2015). Continuous Rotating Belt Filtration for Primary Treatment and Combined
799	Sewer Overflows, (January), 58–62.
800	Heinz, B., Birk, S., Liedl, R., Geyer, T., Straub, K. L., Andresen, J., Kappler, A. (2009). Water
801	quality deterioration at a karst spring (Gallusquelle, Germany) due to combined sewer
802	overflow: Evidence of bacterial and micro-pollutant contamination. Environmental Geology,
803	57(4), 797-808. https://doi.org/10.1007/s00254-008-1359-0
804	Hnaťuková, P. (2011). Geochemical distribution and mobility of heavy metals in sediments of
805	urban streams affected by combined sewer overflows. Journal of Hydrology and

806	Hydromechanics, 59(2), 85-94. https://doi.org/10.2478/v10098-011-0007-7
807	Hofer, T., Montserrat, A., Gruber, G., Gamerith, V., Corominas, L., & Muschalla, D. (2018). A
808	robust and accurate surrogate method for monitoring the frequency and duration of
809	combined sewer overflows. Environmental Monitoring and Assessment, 190(4).
810	https://doi.org/10.1007/s10661-018-6589-3
811	Jalliffier-Verne, I., Heniche, M., Madoux-Humery, A. S., Galarneau, M., Servais, P., Prévost, M.,
812	& Dorner, S. (2016). Cumulative effects of fecal contamination from combined sewer
813	overflows: Management for source water protection. Journal of Environmental
814	Management, 174, 62-70. https://doi.org/10.1016/j.jenvman.2016.03.002
815	Jotte, L., Raspati, G., & Azrague, K. (2017). Report Review of Stormwater Management.
816	Jung, C., Oh, J., & Yoon, Y. (2015). Removal of acetaminophen and naproxen by combined
817	coagulation and adsorption using biochar: influence of combined sewer overflow
818	components. Environmental Science and Pollution Research, 22(13), 10058–10069.
819	https://doi.org/10.1007/s11356-015-4191-6
820	Kistemann, T., Schmidt, A., & Flemming, H. C. (2016). Post-industrial river water quality-Fit
821	for bathing again? International Journal of Hygiene and Environmental Health, 219(7),
822	629-642. https://doi.org/10.1016/j.ijheh.2016.07.007
823	Kumordzi, G., Malekshoar, G., Yanful, E. K., & Ray, A. K. (2016). Solar photocatalytic
824	degradation of Zn2+using graphene based TiO2. Separation and Purification Technology,
825	168, 294–301. https://doi.org/10.1016/j.seppur.2016.05.040
826	Launay, M. A., Dittmer, U., & Steinmetz, H. (2016). Organic micropollutants discharged by

827 combined sewer overflows – Characterisation of pollutant sources and stormwater-related

828	processes. Water Research, 104, 82-92. https://doi.org/10.1016/j.watres.2016.07.068
829	Levy, Z. F., Smardon, R. C., Bays, J. S., & Meyer, D. (2014). A point source of a different color:
830	Identifying a gap in united states regulatory policy for "green" CSO treatment using
831	constructed wetlands. Sustainability (Switzerland), 6(5), 2392-2412.
832	https://doi.org/10.3390/su6052392
833	Li, T., Tan, Q., & Zhu, S. (2010). Characteristics of combined sewer overflows in Shanghai and
834	selection of drainage systems. Water and Environment Journal, 24(1), 74-82.
835	https://doi.org/10.1111/j.1747-6593.2008.00141.x
836	Madoux-Humery, AS., Dorner, S. M., Sauvé, S., Aboulfadl, K., Galarneau, M., Servais, P., &
837	Prévost, M. (2015). Temporal analysis of E. coli, TSS and wastewater micropollutant loads
838	from combined sewer overflows: implications for management. Environmental Science:
839	Processes & Impacts, 17(5), 965-974. https://doi.org/10.1039/C5EM00093A
840	Madoux-Humery, A. S., Dorner, S., Sauvé, S., Aboulfadl, K., Galarneau, M., Servais, P., &
841	Prévost, M. (2016). The effects of combined sewer overflow events on riverine sources of
842	drinking water. Water Research, 92, 218–227. https://doi.org/10.1016/j.watres.2015.12.033
843	Mailhot, A., Talbot, G., & Lavallée, B. (2015). Relationships between rainfall and Combined
844	Sewer Overflow (CSO) occurrences. Journal of Hydrology, 523, 602-609.
845	https://doi.org/10.1016/j.jhydrol.2015.01.063
846	Masi, F., Rizzo, A., Bresciani, R., & Conte, G. (2017). Constructed wetlands for combined sewer
847	overflow treatment: Ecosystem services at Gorla Maggiore, Italy. Ecological Engineering,
848	98, 427-438. https://doi.org/10.1016/j.ecoleng.2016.03.043

849 Maté Marín, A., Rivière, N., & Lipeme Kouyi, G. (2018). DSM-flux: A new technology for

850	reliable Combined Sewer Overflow discharge monitoring with low uncertainties. Journal of
851	Environmental Management, 215, 273–282. https://doi.org/10.1016/j.jenvman.2018.03.043
852	McBride, G. B., Stott, R., Miller, W., Bambic, D., & Wuertz, S. (2013). Discharge-based QMRA
853	for estimation of public health risks from exposure to stormwater-borne pathogens in
854	recreational waters in the United States. Water Research, 47(14), 5282–5297.
855	https://doi.org/10.1016/j.watres.2013.06.001
856	McFadden, M., Loconsole, J., Schockling, A. J., Nerenberg, R., & Pavissich, J. P. (2017).
857	Comparing peracetic acid and hypochlorite for disinfection of combined sewer overflows:
858	Effects of suspended-solids and pH. Science of the Total Environment, 599-600, 533-539.
859	https://doi.org/10.1016/j.scitotenv.2017.04.179
860	McGinnis, S., Spencer, S., Firnstahl, A., Stokdyk, J., Borchardt, M., McCarthy, D. T., & Murphy,
861	H. M. (2018). Human Bacteroides and total coliforms as indicators of recent combined
862	sewer overflows and rain events in urban creeks. Science of the Total Environment, 630,
863	967–976. https://doi.org/10.1016/j.scitotenv.2018.02.108
864	McSweeney, C., Kang, S., Gagen, E., Davis, C., Morrison, M., & Denman, S. (2009). Recent
865	developments in nucleic acid based techniques for use in rumen manipulation. Revista
866	Brasileira de Zootecnia, 38, 341-351. Retrieved from http://orton.catie.ac.cr/cgi-
867	bin/wxis.exe/?IsisScript=SCBR.xis&method=post&formato=2&cantidad=1&
868	amp;expresion=mfn=025288
869	Meyer, D., Molle, P., Esser, D., Troesch, S., Masi, F., & Dittmer, U. (2013). Constructed
870	wetlands for combined sewer overflow treatment-comparison of German, French and Italian
871	approaches. Water (Switzerland), 5(1), 1-12. https://doi.org/10.3390/w5010001

872	Montserrat, A., Bosch, L., Kiser, M. A., Poch, M., & Corominas, L. (2015). Using data from
873	monitoring combined sewer overflows to assess, improve, and maintain combined sewer
874	systems. Science of the Total Environment. https://doi.org/10.1016/j.scitotenv.2014.10.087
875	Montserrat, A., Gutierrez, O., Poch, M., & Corominas, L. (2013). Field validation of a new low-
876	cost method for determining occurrence and duration of combined sewer overflows. Science
877	of the Total Environment, 463–464, 904–912.
878	https://doi.org/10.1016/j.scitotenv.2013.06.010
879	Morgan, D., Xiao, L., & McNabola, A. (2017). Evaluation of combined sewer overflow
880	assessment methods: case study of Cork City, Ireland. Water and Environment Journal,
881	<i>31</i> (2), 202–208. https://doi.org/10.1111/wej.12239
882	Morris, G. (1999). Regulatory requirements: the EA view. Developments in Storm Sewage
883	Management: Meeting the Challenge of AMP3. CIWEM Conf. Wakefield, UK.
884	Munro, K., Martins, C. P. B., Loewenthal, M., Comber, S., Cowan, D. A., Pereira, L., & Barron,
885	L. P. (2019). Evaluation of combined sewer overflow impacts on short-term pharmaceutical
886	and illicit drug occurrence in a heavily urbanised tidal river catchment (London, UK).
887	Science of The Total Environment, 657, 1099–1111.
888	https://doi.org/10.1016/j.scitotenv.2018.12.108
889	Musolff, A., Leschik, S., Möder, M., Strauch, G., Reinstorf, F., & Schirmer, M. (2009). Temporal
890	and spatial patterns of micropollutants in urban receiving waters. Environmental Pollution,
891	157(11), 3069–3077. https://doi.org/10.1016/j.envpol.2009.05.037
892	Nielsen, P. H., Raunkjær, K., Norsker, N. H., Jensen, N. A., & Hvitved-Jacobsen, T. (1992).
893	Transformation of Wastewater in Sewer Systems – A Review. Water Science and

894	Technology, 25(6), 17-31. https://doi.org/10.2166/wst.1992.0111
895	Nurizzo, C., Antonelli, M., Profaizer, M., & Romele, L. (2005). By-products in surface and
896	reclaimed water disinfected with various agents. Desalination, 176(1-3 SPEC. ISS.), 241-
897	253. https://doi.org/10.1016/j.desal.2004.11.012
898	Pálfy, T. G., Meyer, D., Troesch, S., Gourdon, R., Olivier, L., & Molle, P. (2018). A single-
899	output model for the dynamic design of constructed wetlands treating combined sewer
900	overflow. Environmental Modelling and Software, 102, 49–72.
901	https://doi.org/10.1016/j.envsoft.2017.12.023
902	Pálfy, T. G., Molle, P., Langergraber, G., Troesch, S., Gourdon, R., & Meyer, D. (2016).
903	Simulation of constructed wetlands treating combined sewer overflow using
904	HYDRUS/CW2D. Ecological Engineering, 87, 340–347.
905	https://doi.org/10.1016/j.ecoleng.2015.11.048
906	Passerat, J., Ouattara, N. K., Mouchel, J. M., Vincent Rocher, & Servais, P. (2011). Impact of an
907	intense combined sewer overflow event on the microbiological water quality of the Seine
908	River. Water Research, 45(2), 893–903. https://doi.org/10.1016/j.watres.2010.09.024

- Phillips, J. P., Chalmers, T. A., Gray, L. J., Kolpin, W. D., Foreman, T. W., & Wall, R. G.
- 910 (2012). Combined Sewer Overflows: An Environmental Source of Hormones and
- 911 Wastewater Micropollutants. *Environmental Science & Technology*, *46*(10), 5336–5343.
- 912 https://doi.org/10.1021/es3001294
- 913 Phillips, P., & Chalmers, A. (2009). Wastewater effluent, combined sewer overflows, and other
- sources of organic compounds to Lake Champlain. *Journal of the American Water*
- 915 *Resources Association*, 45(1), 45–57. https://doi.org/10.1111/j.1752-1688.2008.00288.x

- Pond, K. (2005). Water recreation and disease: Plausibility of associated infections: Acute *effects, sequelae and mortality.* IWA Publishing.
- 918 Riechel, M., Matzinger, A., Pawlowsky-Reusing, E., Sonnenberg, H., Uldack, M., Heinzmann,
- B., ... Rouault, P. (2016). Impacts of combined sewer overflows on a large urban river –
- 920 Understanding the effect of different management strategies. *Water Research*, 105, 264–
- 921 273. https://doi.org/10.1016/j.watres.2016.08.017
- 922 Riechel, M., Seis, W., Matzinger, A., Pawlowsky-Reusing, E., & Rouault, P. (2019). Relevance
- 923 of Different CSO Outlets for Bathing Water Quality in a River System. In G. Mannina (Ed.)
- 924 (pp. 859–863). Springer. https://doi.org/10.1007/978-3-319-99867-1_148
- 925 Rizzo, A., Bresciani, R., Masi, F., Boano, F., Revelli, R., & Ridolfi, L. (2018). Flood reduction as
- an ecosystem service of constructed wetlands for combined sewer overflow. *Journal of*

927 *Hydrology*, 560, 150–159. https://doi.org/10.1016/j.jhydrol.2018.03.020

- Rouff, A. A., Eaton, T. T., & Lanzirotti, A. (2013). Heavy metal distribution in an urban wetland
- impacted by combined sewer overflow. *Chemosphere*, 93(9), 2159–2164.
- 930 https://doi.org/10.1016/j.chemosphere.2013.07.077
- Ruggaber, T. P., & Talley, J. W. (2005). Detection and Control of Combined Sewer Overflow

932 Events Using Embedded Sensor Network Technology, 1–12.

- 933 https://doi.org/10.1061/40792(173)306
- Ruppelt, J. P., Tondera, K., Vorenhout, M., Van der Weken, L., & Pinnekamp, J. (2019). Redox
- 935 potential as a method to evaluate the performance of retention soil filters treating combined
- sewer overflows. *Science of the Total Environment*, 650, 1628–1639.
- 937 https://doi.org/10.1016/j.scitotenv.2018.09.043

938	Ryu, J., Oh, J., Snyder, S. A., & Yoon, Y. (2014). Determination of micropollutants in combined
939	sewer overflows and their removal in a wastewater treatment plant (Seoul, South Korea).
940	Environmental Monitoring and Assessment, 186(5), 3239–3251.
941	https://doi.org/10.1007/s10661-013-3613-5
942	Sandoval, S., Torres, A., Pawlowsky-Reusing, E., Riechel, M., & Caradot, N. (2013). The
943	evaluation of rainfall influence on combined sewer overflows characteristics: The Berlin
944	case study. Water Science and Technology, 68(12), 2683–2690.
945	https://doi.org/10.2166/wst.2013.524
946	Schares, G., Pantchev, N., Barutzki, D., Heydorn, A. O., Bauer, C., & Conraths, F. J. (2005).
947	Oocysts of Neospora caninum, Hammondia heydorni, Toxoplasma gondii and Hammondia
948	hammondi in faeces collected from dogs in Germany. International Journal for
949	Parasitology, 35(14), 1525–1537. https://doi.org/10.1016/j.ijpara.2005.08.008
950	Schertzinger, G., Ruchter, N., & Sures, B. (2018). Metal accumulation in sediments and
951	amphipods downstream of combined sewer overflows. Science of the Total Environment,
952	616-617, 1199-1207. https://doi.org/10.1016/j.scitotenv.2017.10.199
953	Scheurer, M., Heß, S., Lüddeke, F., Sacher, F., Güde, H., Löffler, H., & Gallert, C. (2015).
954	Removal of micropollutants, facultative pathogenic and antibiotic resistant bacteria in a full-
955	scale retention soil filter receiving combined sewer overflow. Environmental Sciences:
956	Processes and Impacts, 17(1), 186–196. https://doi.org/10.1039/c4em00494a
957	Seis, W., Zamzow, M., Caradot, N., & Rouault, P. (2018). On the implementation of reliable
958	early warning systems at European bathing waters using multivariate Bayesian regression
959	modelling. Water Research, 143, 301-312. https://doi.org/10.1016/j.watres.2018.06.057

960	Soriano, L., & Rubió, J. (2019). Impacts of Combined Sewer Overflows on surface water bodies.
961	The case study of the Ebro River in Zaragoza city. Journal of Cleaner Production, 226, 1–5.
962	https://doi.org/10.1016/j.jclepro.2019.04.033
963	Stott, R., Tondera, K., Blecken, GT., & Schreiber, C. (2018). Microbial Loads and Removal
964	Efficiency Under Varying Flows. In K. Tondera, GT. Blecken, F. Chazarenc, & C. C.
965	Tanner (Eds.) (pp. 57–74). Cham: Springer International Publishing.
966	https://doi.org/10.1007/978-3-319-70013-7_4
967	Suárez, J., & Puertas, J. (2005). Determination of COD, BOD, and suspended solids loads during
968	combined sewer overflow (CSO) events in some combined catchments in Spain. Ecological
969	Engineering, 24(3), 201-219. https://doi.org/10.1016/j.ecoleng.2004.11.005
970	Tabuchi, J SIAAP's stormwater management policy" Impacts of combined sewer overflows on
971	urban waters: Challenges and solutions for European cities Amsterdam (2013).
972	Tanaka, K., & Takada, H. (2016). Microplastic fragments and microbeads in digestive tracts of
973	planktivorous fish from urban coastal waters. Scientific Reports, 6(March), 1-8.
974	https://doi.org/10.1038/srep34351
975	Tao, J., Mancl, K. M., & Tuovinen, O. H. (2010). Attenuation of pollutants in sanitary sewer
976	overflow: Comparative evaluation of treatment with fixed media bioreactors. Bioresource
977	Technology, 101(6), 1781–1786. https://doi.org/10.1016/j.biortech.2009.10.038
978	Tondera, K. (2017). Evaluating the performance of constructed wetlands for the treatment of
979	combined sewer overflows. <i>Ecological Engineering</i> , (October), 1–7.
980	https://doi.org/10.1016/j.ecoleng.2017.10.009
981	Tondera, K., Klaer, K., Gebhardt, J., Wingender, J., Koch, C., Horstkott, M., Pinnekamp, J.

982 ((2015).	Reducin	g pathogens	s in	combined	sewer	overflows	using	ozonation	or	U٧
J02 (20157.	neuuem	z pamozon	5 III	comonica	30 11 01	0,0110,03	using	ozonation	or	U

- 983 irradiation. International Journal of Hygiene and Environmental Health, 218(8), 731–741.
 984 https://doi.org/10.1016/j.ijheh.2015.09.002
- ⁹⁸⁵ Tondera, K., Klaer, K., Roder, S., Brueckner, I., Strathmann, M., Kistemann, T., ... Pinnekamp,
- J. (2016). Developing an easy-to-apply model for identifying relevant pathogen pathways
- 987 into surface waters used for recreational purposes. International Journal of Hygiene and

988 Environmental Health, 219(7), 662–670. https://doi.org/10.1016/j.ijheh.2015.11.005

- ⁹⁸⁹ Tondera, K., Koenen, S., & Pinnekamp, J. (2013). Survey monitoring results on the reduction of
- 990 micropollutants, bacteria, bacteriophages and TSS in retention soil filters. *Water Science*

991 *and Technology*, 68(5), 1004–1012. https://doi.org/10.2166/wst.2013.340

- ⁹⁹² Tondera, K., Ruppelt, J. P., Pinnekamp, J., Kistemann, T., & Schreiber, C. (2019). Reduction of
- 993 micropollutants and bacteria in a constructed wetland for combined sewer overflow
- treatment after 7 and 10 years of operation. *Science of the Total Environment*, 651, 917–927.
- 995 https://doi.org/10.1016/j.scitotenv.2018.09.174
- U.S. EPA. (2001). Report to Congress Implementation and Enforcement of the Combined Sewer
 Overflow Control Policy, (December).
- U.S.EPA. (2004). Report to Congress on Impacts and Control of Combined Sewer Overflows and
- Sanitary Sewer Overflows Fact Sheet. *Washington D.C.*, 1–2.
- 1000 https://doi.org/10.1227/01.NEU.0000028680.51299.00
- 1001 UBA. (2012). Die Wasserrahmenrichtlinie Eine Zwischenbilanz zur Umsetzung der
- 1002 Maßnahmenprogramme.
- 1003 USEPA. (2018). Smart Data Infrastructure for Wet Weather Control and Decision Support EPA

1004 **830- B-17-004, 2018.**

1005	Viviano.	G.,	Valsecchi.	S.	. Polesello.	S	Ca	odaglio	. A.	. Tartari.	G.	. & Salerno.	F. ((2017)).
T 0 0 0	, , , , , , , , , , , , , , , , , , , ,	. .,	, and county	~.		, ~.,	Cu	Jourgino	,	,		, ee saierno,		(=0 + 7 /	<i></i>

- 1006 Combined Use of Caffeine and Turbidity to Evaluate the Impact of CSOs on River Water
- 1007 Quality. Water, Air, and Soil Pollution, 228(9). https://doi.org/10.1007/s11270-017-3505-3
- 1008 Vymazal, J. (2011). Constructed Wetlands for Wastewater Treatment: Five Decades of
- 1009 Experience †. *Environmental Science & Technology*, 45(1), 61–69.
- 1010 https://doi.org/10.1021/es101403q
- 1011 Warner, W., Nödler, K., Farinelli, A., Blum, J., & Licha, T. (2018). Integrated approach for
- 1012 innovative monitoring strategies of reservoirs and lakes. *Environmental Engineering and*
- 1013 *Management Journal*, 17(10), 2497–2505. https://doi.org/10.30638/eemj.2018.248
- 1014 WHO. (2008). Guidelines for drinking-water quality.
- 1015 Willems, P. (2012). Impacts of Climate Change on Rainfall Extremes and Urban Drainage
- 1016 Systems. *Water Intelligence Online*, *11*(1), 16–28. https://doi.org/10.2166/9781780401263
- 1017 Xu, Z., Wu, J., Li, H., Chen, Y., Xu, J., Xiong, L., & Zhang, J. (2018). Characterizing heavy
- 1018 metals in combined sewer overflows and its influence on microbial diversity. *Science of the*

1019 *Total Environment*, 625, 1272–1282. https://doi.org/10.1016/j.scitotenv.2017.12.338

- 1020 Young, S., Juhl, A., & O'Mullan, G. D. (2013). Antibiotic-resistant bacteria in the Hudson River
- 1021 Estuary linked to wet weather sewage contamination. *Journal of Water and Health*, 11(2),
- 1022 297–310. https://doi.org/10.2166/wh.2013.131
- 1023
- 1024

1025 Figure captions

- **Fig. 1.** A) Separate sewer system, B) Combined sewer system, C) Combined sewer overflow
- 1027 (adopted from Al Aukidy et al., 2017).





1030 Fig. 2. Management strategies for combined sewer overflow (adopted from Levy et al., 2014).

1033 Fig. 3. Location of the INTCATCH pilot plant in Lazise, Villa Bagatta





Fig. 4. Flow diagram of pilot plant in Villa Bagatta – INTCATCH (Botturi et al., 2020)